

# 4MP IR PTZ Network Camera with Analytics+

## 45x Starlight PTZ Network Camera



- 1/1.8-in. 8 MP Progressive Scan STARVIS™ CMOS Sensor
- Powerful 40x Optical Zoom Lens
- Smart H.265+ and Smart H.264+ Dual Codecs
- 8 MP at 30 fps Maximum Resolution
- Analytics+ Functions — Face Recognition and Perimeter Protection
- Starlight Technology for Ultra-low Light Sensitivity
- Maximum IR Distance up to 500 m (1640 ft)
- Predictive Focus Analysis (PFA) Technology
- ArcticPro Series Camera - Operational down to  $-40^{\circ}\text{C}$  ( $-40^{\circ}\text{F}$ )
- IP67 Ingress Protection
- Integrated Smart Wiper
- Intelligent Video System with Auto-tracking
- Supports Dahua Proprietary Hi-PoE Power Source
- Five-year Warranty\*



### System Overview

The 4K IR PTZ Dome camera features a 1/1.8-in STARVIS™ CMOS imager with a 40x optical zoom lens, and provides an all in one solution for capturing long-distance video surveillance for outdoor applications. The camera offers Analytics+ functions at the edge – performing complex real-time face recognition and perimeter protection surveillance. The Dahua Analytics+ algorithms significantly improve accuracy and reliability as compared to standard intelligent features.

### Functions

#### Face Recognition

The camera includes human facial feature extraction, real-time facial snapshots, and supports a database of up to 10,000 face images. The feature enables a pro-active way to identify persons of interest before an incident occurs. The advanced processor extracts and categorizes various features, including age, gender, expression, and whether the target face wears glasses or sports facial hair. The camera is ideal for applications that require entrance/exit management, where knowing who is coming and going is a valuable asset.

#### Perimeter Protection

Dahua Analytics+ includes Tripwire and Intrusion functions that offer custom tripwires based on object type for automation in limited access areas. Perimeter Protection requires less pixels to detect an object to deliver improved accuracy and decreased false alarms due to lights, weather, trees, or animals.

#### Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers light sensitivity that captures details in low light down to 0.002 lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

#### Auto-tracking

This feature controls the pan/tilt/zoom actions of the camera to automatically track an object in motion and to keep it in the scene. The tracking action can be triggered manually or automatically by defined rules. Once a rule is triggered, the camera can zoom in and track the defined target automatically.

#### Predictive Focus Analysis Technology

The camera uses innovative PFA Technology to improve zoom accuracy and to decrease focus time. A series of advanced algorithms more accurately judge the direction and the distance to a subject, improving picture clarity throughout the zooming process.

#### ArcticPro

The Dahua ArcticPro Series of extreme-environment cameras combine temperature-tolerant components, a waterproof enclosure, and an integrated heater to ensure flawless operation in temperatures as low as  $-40^{\circ}\text{C}$  ( $-40^{\circ}\text{F}$ ). For applications that demand high-resolution video with advanced features in extremely cold environments, the Dahua ArcticPro Series offers a camera to satisfy the most demanding requirements.

#### Environmental

Subjected and certified to rigorous dust and water immersion tests, the IP67 rating makes it suitable for demanding outdoor applications.

#### Protection

The camera allows for  $\pm 25\%$  input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 8KV lightning rating provides effective protection for both the camera and its structure against lightning.



Technical Specification			
Camera			
Image Sensor	1/1.8-in. STARVIS™ CMOS		
Effective Pixels	3840(H) x 2160(V), 8 MP		
RAM/ROM	1024 MB / 128 MB		
Scanning System	Progressive		
Electronic Shutter Speed	1/1 s to 1/30,000 s		
Minimum Illumination	Color: 0.002 lux at F1.4 B/W: 0.0002 lux at F1.4 0 Lux with IR on		
IR Distance	Distance up to 500.0 m (1640.42 ft)		
IR On/Off Control	Auto, Manual		
IR LEDs	10		
Lens			
Focal Length	5.6 mm to 223 mm		
Max. Aperture	F1.4 to F4.8		
Angle of View	Horizontal: 63.9° to 2.0° Vertical: 37.2° to 1.2° Diagonal: 71.2° to 2.4°		
Optical Zoom	40x		
Focus Control	Auto, Manual		
Iris Control	Auto, Manual		
Close Focus Distance	100 mm to 1000 mm (3.93 in. to 39.37 in.)		
DORI Distance <sup>1</sup>			
Detect	Observe	Recognize	Identify
4400 m (14,435 ft)	1740 m (5708 ft)	880 m (2887 ft)	440 m (1443 ft)
PTZ			
Pan/Tilt Range	Pan: 0° to 360° endless Tilt: -30° to 90° Auto Flip 180°		
Manual Control Speed	Pan: 0.1° to 240° /s Tilt: 0.1° to 100° /s		
Preset Speed	Pan: 240° /s Tilt: 120° /s		
Presets	300		
PTZ Mode	5 Pattern, 8 Tour (up to 32 presets per tour), Auto Pan, Auto Scan		
Speed Setup	Human-oriented focal Length/ speed adaptation		
Power up Action	Auto restore to previous PTZ and lens status after power failure		
Idle Motion	Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period		
Protocol	DH-SD, Pelco-P/D (Auto recognition)		
Video			
Compression	Smart H.265+, H.265, Smart H.264+, H.264, MJPEG (sub stream only)		
Streaming Capability	Three (3) Streams		
Resolution	8 MP (3840 x 2160), 1080p (1920 x 1080), 1.3 MP (1280 x 960), 720p (1280 x 720), D1 (704 x 380), CIF (352 x 240)		

Frame Rate	Main Stream	8 MP, 1080p, 1.3 MP, or 720p at 30 fps
	Sub Stream 1	D1 or CIF at 30 fps
	Sub Stream 2	1080p, 1.3 MP, or 720p at 30 fps
Bit Rate Control		CBR, VBR
Bit Rate		H.265 / H.264: 512 K to 8192 Kbps,
Day/Night		Auto (ICR), Color, B/W
Backlight Compensation		BLC, HLC, True WDR (120 dB)
White Balance		Auto, ATW, Indoor, Outdoor, Manual, Sodium Lamp, Natural, Street Lamp
Gain Control		Auto, Manual, Gain Priority, Shutter Priority, Aperture Priority
Noise Reduction		Ultra DNR (2D/3D)
Advanced Features		Motion Detection, Region of Interest, Electronic Image Stabilization (EIS), Defog
Digital Zoom		16x
Flip		180°
Privacy Masking		Up to 24 areas
Audio		
Compression		G.711a, G.711Mu, PCM, G.726, AAC, G722.1, G.729, MPEG2-Layer2
Network		
Ethernet		RJ-45 (10 Base-T/100 Base-TX)
Protocol		IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
Interoperability		ONVIF Profile S and G, API
Streaming Method		Unicast / Multicast
Maximum User Access		20 users
Edge Storage		NAS (Network Attached Storage) Local PC for instant recording Micro SD Card, maximum 256 GB
Web Viewer		Internet Explorer
Management Software		Smart PSS, DSS, DMSS
Mobile Operating System		IOS, Android
Certifications		
CE		EN55032, EN55024, EN50130-4
Electromagnetic Compatibility (EMC)		FCC Part 15 Subpart B ANSI C63.4- 2014
Interface		
Video		One (1) BNC (1.0 Vp-p, 75 Ω)
Audio		Input: One (1) Channel Output: One (1) Channel
RS485		One (1)
Alarm		Input: Seven (7) Channels Output: Two (2) Channels
Electrical		
Power Supply		24 VAC, 3 A (± 25%) or via Dahua proprietary Hi-PoE power source
Power Consumption		26 W, 42 W with IR on

1. The DORI distance is a general proximity of distance helping to pinpoint the correct camera for your needs. The DORI distance is calculated based on sensor specifications and lab test results according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify.

## Environmental

Operating Conditions	-40° C to 70° C (-40° F to +158° F) Less than 95% RH
Ingress Protection	IP67
Construction	
Casing	Metal
Dimensions	ø262.0 mm x 415.60 mm (ø10.32 in. x 16.36 in.)
Net Weight	8.75 kg (18.74 lb)
Gross Weight	13.50 kg (29.76 lb)

## Analytics+ Functions<sup>2</sup>

Face Recognition	<ul style="list-style-type: none"> <li>Supports five group libraries that store up to 10,000 faces on the camera.</li> <li>Captures 16 face images per second, compares to stored images, and produces match statistics.</li> <li>Extracts six attributes and eight expressions from a face capture.</li> <li>Offers face enhancement, face exposure, and a face angle filter for clear facial images.</li> </ul>
Perimeter Protection	<ul style="list-style-type: none"> <li>Detects human or vehicle violations using the following methods:           <ul style="list-style-type: none"> <li>Tripwire: a target crosses a defined line.</li> <li>Intrusion: a target enters or exits a defined perimeter.</li> </ul> </li> <li>Filters actions that may produce a false alarm due to animals, leaves, and bright lights.</li> </ul>

## Intelligent Video System Functions<sup>2</sup>

IVS triggers an alarm and takes a defined action for the following events:	
Standard Features	<ul style="list-style-type: none"> <li>Tampering with the camera.</li> <li>Error writing to an onboard Micro SD card.</li> <li>Error sending or receiving data over the network.</li> <li>Unauthorized access to the camera.</li> <li>IP Address Conflict</li> </ul>
Premium Features	
Motion	An object moves through any part of the scene.
Tripwire	A target crosses a user-defined line.
Intrusion	A target enters or exits a defined perimeter.
Abandoned/Missing Object	A target leaves an object in designated area, or a target removes an object from the same designated area.
Advanced Features	
Auto-tracking	Controls the pan/tilt/zoom actions of the camera to automatically track an object in motion and to keep it in the scene.

## Ordering Information

Type	Part Number	Description
4K PTZ Camera	8A840WANF	4K 40x IR PTZ Starlight Network Camera with Analytics+
Accessories, Included	PFB306W	Wall Mount
	AC24V/3A	Power Adapter
	PFA118	Mount Adapter (use with PFB710C)
	PFA150	Pole Mount
Accessories, Optional	PFB710C	Heavy-duty Ceiling Mount Bracket (use with PFA118)
Accessories, Optional Dahua	PFT1200	Hi-PoE Midspan
	DH-LR2110-8ET-120	8-port ePoE Layer 2 Switch

## Accessories

### Included:



PFB306W  
Wall Mount



AC24V/3A  
Power Adapter

### Optional:



PFA150  
Pole Mount



PFB710C  
Heavy-duty Ceiling Mount



PFA118  
Mount Adapter

<sup>2</sup>. The Face Capture, Perimeter Protection, and IVS functions cannot be used at the same time, only one Analytics+ or IVS function can be used at a time. In addition, the Smart H.265+ and the Smart H.264+ cannot be used simultaneously with either an Analytics+ or an IVS feature.

Dimensions (mm/in.)

