

AVA-TVI-BLN-C
HYBRID BALUN



AVA-TVI-BLN-C HYBRID BALUN

The AVA-TVI-BLN-C is a 1 Ch. HD Hybrid balun up to 820ft on HD-TVI, HD-CVI, AHD, and Analog cameras. Push in terminal connector. Transmits HD and Analog video over twisted pair CAT5E/6E. Pigtail Type

FUNCTIONS

- 1 CH passive HD Hybrid balun up to 820ft. on HD-TVI, HD-CVI, AHD (Up to 5MP), and Analog cameras.
- Push in terminal connection.
- Transmits HD and analog video over twisted pair (Cat5E/6E)
- Plug-and-play solution
- Ultra high frequency with built-in TVS for surge protection
- Exceptional interference rejection with anti-static design
- TVI cameras only require one pair of UTP wire connection

SPECIFICATIONS

PROPERTIES	
Transmission Signal	1 Channel
Transmission Distance	HD-TVI / HD-CVI / AHD Up to 250m (820ft)
Category Type	UTP CAT5 / 5E / 6
VIDEO TRANSMISSION	
Coaxial Video Connector	BNC-M
Twisted-Pair Video Connector	Push-Terminal
Compatible Format	HD-TVI / HD-CVI / AHD / ANALOG (MAGIC)
Resolution	Up to 5MP HD for All Video Formats
Anti-Interference	>60db
PROTECTION	
TVS	Built in TVS for Surge Protection
Coaxial Cable Connector	2KV(common-code) Per : IEC1000-4-5
UTP Cable Connector	2KV(different-code) 4KV(common-code) Per: IEC1000-4-5