

FEATURES

- 5MP Ultra HD Resolution
- NDAA Compliant
- H.265 Compression
- 2.8mm Wide Angle Fixed Lens
- IR Up to 30 Feet
- Built-in Microphone
- IP67 Rated Weatherproof Housing
- ONVIF Compliant
- P2P Support

SPECIFICATIONS

Image Sensor	1/2.7" Progressive CMOS
Effective Pixels	5MP 2592 (H) × 1944 (V)
Intelligence Features	Not Supported
Min. Illumination	Color 0.002Lux @ F1.2 (AGC ON); B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Slow Shutter	Support
Lens	2.8mm
Lens Type	Fixed (M12)
Field of View	Horizontal: 95°
Image Settings	Flip Mode, Saturation, Brightness, Contrast, Hue, Sharpness Adjustable
Day & Night	IR Cut Filter with Auto Switch
Digital Noise	Auto
Reduction	
White Balance	Auto / Manual
WDR	Digital WDR
Backlight Comp.	Off/On (5 Zone)
Video Compression	H.265 / H.264
Video Bit Rate	8Kbps ~ 8Mbps
Bitrate Control	CBR / VBR
Streaming Capability	Dual Stream (Main/Sub)
Motion Detection	Off/On (8 Level)
Privacy Masking	Yes
Ethernet	RJ-45 (10/100 BASE-T)
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, UDP, NTP, UPnP, IGMP, ICMP, SNMP, HTTPS, FTP
IP	IPv6 / IPv4
Compatibility	ONVIF (Profile S, Profile G)
IR Range	Up to 30 Feet
EDGE Recording	Yes
Alarm	Not Supported
Audio	Built-in Microphone

 **BOLIDE**
TECHNOLOGY GROUP

POE	Yes
Weather Rating	IP67, IK10
Resolution	Main Stream: 5MP (2592x1944) (1~15FPS) 4MP (2592x1520) (1~15FPS) 3MP (2304x1296) (1~15FPS) 1080P(1920x1080) (1~15FPS) 720P(1280x720) (1~15FPS) Sub Stream: VGA (640x480) (1~10FPS) QVGA (320x240) (1~10FPS)
Power Supply	D12V/POE(IEEE802.3af)
Consumption	≤ 7W
Reset Button	No
Operating	-40 ~ +140°F / less than ≤ 95% RH
Homologation	CE, FCC, EN – 50155 IEC-60068-2
MTBF	60000 HRS
Temperature	
Storage	-40 ~ +131°F
Temperature	
Dimensions	4.72" x 2.51"
Net Weight	0.83lb