

TC-S1283WHX

PTZ Camera



- Full HD (1080p) resolution
- True WDR
- DIS (Digital Image Stabilizer)
- AF optical zoom Lens (f=4.3mm ~ 129mm), 30X zoom
- Motion Detection
- IP66 supports
- Day&Night (ICR)
- De-fog
- Coaxial OSD Control

SPECIFICATIONS

Video	
Imager Sensor	1/2.8" SONYSTARVIS CMOS Sensor
Effective pixels	1945(H) X 1097(V), 2.13MP
Total pixels	1945(H) X 1109(V), 2.16MP
Max. Resolution	1920X1080
Scanning Mode	Progressive Scan
Lens Type	AF Zoom lens
Focal Length	f = 4.3mm ~ 129mm
IRIS Control	DCAuto Iris
Angular Field of View	65.1°-2.23°(H)
Min. illumination	COLOR 0.35 Lux BW: 0.013Lux@ 50IRE
Electronic Shutter Speed	Auto(1/30,000 ~ x8 sec), Manual
Day/Night	YES(ICR)
Video Out	1 HD BNC, 1 SDBNC
PAN / TILT / ROTATE	
Pan Range	360° (Endless)
Pan Speed	Max 380° / sec (Preset)
Tilt Range	-10° ~ 190°
Tilt Speed	Max 380° / sec (Preset)
Preset	240ea
Function	
AGC	0 ~ 7 Level Adjustable
Brightness	0 ~ 20 Level Adjustable
Sens-UP	OFF/ x2 ~ x8
WDR(Wide Dynamic Range)	True WDR(OFF/ ON, NIGHTOFF(Low, Middle, High))
Backlight Compensation(BLC)	OFF/ON
HSBLC	HLCON OFF Level 0~20, COLOR BLACK WHITE YELLOW CYAN GREEN MAGENTA RED BLUE
ACE(D-WDR/ATR-EX)	OFF/LOW MIDDLE HIGH
Motion Detection	OFF/ON (Preset Setup)
Alarm In / Out	Input 4ea / Output 1ea
Privacy Masking	OFF/ON (16 Zone)
White Balance	Auto, Manual (Incandescent Fluorescent Outdoor)
Digital Noise Reduction	2D 3DNR OFF/LOW MIDDLE HIGH
Mirror	OFF/ON
D-ZOOM(EZOOM)	X1 ~ X8
Sharpness	0~10 Level Adjustable
De-fog	OFF/ON
GAMMA Correction	0 ~ 4
Lens Shading(LSC)	OFF/ON
Environmental	
Out-door Ready	IP66
Operating Temperature	-30°C ~ +55°C (-22°F ~ +131°F) (Humidity : 0% ~ 95%)
Electrical	
Power Source	12VDC/ 24VAC (Heater & Fan 24VAC)
Power Consumption	12.0W (Heater & Fan 50.0W)
Mechanical	
Dimensions ((Ø x H)	Ø234mm x 301mm (Ø9.2" x 11.8")



PRODUCT IMAGE



DIMENSIONS

(Unit - mm)

