

DH-2018P

DirectIP® PoE Switch



- Individual port data transmission to DirectIP® NVR
- PoE (IEEE 802.3af, IEEE 802.3at) compliant
- Central power control for greater network utility
- Supports 16 RJ45 ports

Maximum per-device PoE delivery of 140W available for 1~16 RJ45 ports

SPECIFICATIONS

Network	
Service Port	16 RJ45 Connectors (10/100BASE-T)
Uplink Port	2 RJ45 Connectors (10/100/1000BASE-T)
Supported Standards	IEEE 802.3af-2003 / IEEE 802.3at-2009
PD Connection	Up to 16 IEEE 802.3af PDs or up to 4 IEEE 802.3at PDs
PSE Power	140W
General	
Switching Capacity	7.2Gbps
Memory	256MB SDRAM / 32MB Flash
Environmental	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Electrical	
Power Input	100-240V~, 50/60Hz, 2.0-1.0A, 160W
Power Consumption	160W
Approval	FCC CE, KQ, UL, CB
Mechanical	
Dimensions (W x H x D)	430mm x 44mm x 180mm (17.0" x 1.7" x 7.1")
Weight	2.05Kg (4.52lb)



PRODUCT IMAGE



DIMENSIONS

Unit - mm (inch)

