

DH-2212PF

DirectIP® Gigabit PoE Switch



- Individual port for data transmission to DirectIP® NVR
- PoE (IEEE 802.3af, IEEE 802.3at) compliant
- Maximum per-device PoE delivery of 140W available for 1~8 RJ45 ports
- Central power control for greater network utility
- Supports 10 RJ45 ports and 2 SFP slots

SPECIFICATIONS

System	
CPU	EmbeddedMIPS
System Memory	256MBSDRAM32MBFlash
Switching Capacity	24Gbps
Connectivity	
Copper Service Port	8 RJ45Connectors(10/100/1000BASET)
Copper Uplink Port	2 RJ45Connectors(10/100/1000BASET)
Optical Uplink Port	2 SFPSlot(1000BASEX)
PoE Power	
supported Standards	IEEE802.3af-2003 / IEEE802.3at-2009
PD Connection	Up to 8 IEEE802.3af PDsor up to 4 IEEE802.3at PDs
PSE Power Budget	140W
General	
Diemensions(W x H x D)	280mm x 44mm x 180mm (11.0 x 1.7 x 7.1)
Weight	1.55Kg(3.42lb)
Operation Temperature	0°C~ 40°C (32°F ~ 104°F)
Power Input	AC100-240V, 2.0~1.0A 50/60Hz
Power Consumption	160W
Approvals	FCCCEKQULCB



PRODUCT IMAGE



DIMENSIONS

