

DP-DE2108

8Ch HD Encoder



- Supports PTZ Control with UTC Protocol
- Supports 4 Audio input ports
- Supports Analog (CVBS), TVI, and AHD formats
- Supports Quadruple stream

SPECIFICATIONS

Video	
Video Inputs	8 BNC
Max. Resolution	2560 x 1920
Network	
Video Compression	H.265, H.264
Max. Frame Rate	240ips@1080P, 144ips@3MP, 120ips@4MP, 80ips@5MP
Multi-video Streaming	QuadrupleStreaming
Ethernet	RJ45(10/100/1000 BASET)
Alarm and Event	
Trigger Event	Motion Detection, Tampering Trip Zone, Video Loss
Event Notification	RemoteSW, Email(with Image)
Interface	
Audio In / Out	4 / -
Environmental	
Operating Temperature	0°C~40°C(+32°F~+104°F)
Operating Humidity	0%~90%
Electrical	
Power Source	12VDCPoE(IEEE802.3af (Class3))
Power Consumption	12V _s , 0.8A, 10WPoE, IEEE802.3af(Class3), 10W
Approval	FCCCE, KC
Mechanical	
Dimensions	200mm x 44mm x 165.2mm(7.9" x 1.7" x 6.5")
Weight	0.81kg(1.79lb)



PRODUCT IMAGE



DIMENSIONS

Unit - mm (inch)

