

# DV-1304

## 4ch AI in the Box



- Powered by the most advanced IDIS Deep-Learning Analytics (IDLA)
- Heatmap
- Generates real-time event notifications with high accuracy
- Rapid DirectIP plug-and-play installation
- People Counting and Occupancy Control
- Social Distancing Violation
- Live Occupancy Dashboard to maintain capacity limits
- Simply connect to an IDIS NVR
- Queue Monitoring
- Mask Rule Violation
- Dashboard Reporting for visitor flow, checkout traffic, and compliance adherence
- Supports 4-ch IP cameras

### SPECIFICATIONS

Video	
Video Inputs	4 IP Channels
Supported Device	DirectIPNVR
VA Support	PeopleCounting OccupancyControl QueueMonitoring HeatmapSocialDistancing Violation MaskRuleViolation
Network	
Video Compression	H.265, H.264
Network Connection	100M Ethernet x 1 (100BaseTX) with PD 100M Ethernet x 1 (100BaseTX) with PSE(PSEneed Adaptor)
Environmental	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Input	48V=, PoE
Power Consumption	48V=, 0.8A, 38.4WPoE IIEE802.3at(Class4), 25WDCOUTPUT: 48V=, 0.35A MAX
Approval	FCCE KC
Mechanical	
Unit Dimensions (W x H x D)	200mm x 44mm x 157.6mm(7.9' x 1.7' x 6.2')
Unit Weight	0.88kg (1.94lb)



### PRODUCT IMAGE



### DIMENSIONS

Unit - mm (inch)

