

GV-IO Box 4 Ports



- 4 inputs and 4 outputs
- Connectivity of up to 9 units of GV-IO Box 4 / 8 / 16 ports
- A USB port for PC connection (max. 30V DC, 3A output)

GV-IO Box 4 Ports provides 4 inputs and 4 relay outputs. It supports both DC and AC output voltages, and provides a USB port for PC connection.

Specifications

OS Supported	32-bit	Windows XP / Vista / 7 / 8 / 8.1 / 10 / Server 2008	
	64-bit	Windows 7 / 8 / 8.1 / 10 / Server 2008 R2 / Server 2012 / Server 2012 R2	
Compatible S/W		GV-DVR / NVR / VMS, GV-Center V2	
Input	Input	4	
	Input Signal	Dry Contact Wet Contact, 9-30V AC/DC	
Communication	Relay Output	4	
	Relay Status	Normal open	
	Relay Capacitance	USB Connection	30V DC, 3A
RS-485 Connection		125 / 250V AC, 3A 30V DC, 3A	
DC IN		DC 12V, 1A	
Address		0-9, A-F	
Terminal Resistance		120 ohm	
Environmental Conditions		0 ~ 50 °C / 32 ~ 122 °F 5% ~ 95% (non-condensing)	
Dimensions (W x H x D)		111.4 x 27.5 x 101 (mm) / 4.39 x 1.08 x 3.98 (in)	

Note: All specifications are subject to change without notice.

Packing List

1. GV-IO Box x 1
2. USB Cable (Type A to B) x 1
3. Terminal Resistor x 1
4. Power Adapter DC 12V x 1

Diagram

