

8MP TiOC Network Eyeball Camera

Active Alarm and Dual Illuminators with Analytics+



Wiz Sense

WizSense Series devices combine Dahua's powerful Analytics+ with an intuitive and easy to use interface. WizSense devices offer Smart Motion Detection and Perimeter Protection functions that focus on human and vehicular images and ignore irrelevant images to capture important video while reducing false alarms. WizSense Series devices provide powerful general surveillance for small to medium size businesses at a sensible price.

System Overview

The Dahua Three-in-One Camera (TiOC) offers multiple features working in tandem to assist with deterrence and low-light detection while delivering high-resolution video images. The camera also features Perimeter Protection and Smart Motion Detection that offer accurate analytics. The camera is ideal for a host of diverse applications — Enhanced Starlight Technology, True Wide Dynamic Range, and Smart Dual illuminators allow the camera to operate in any lighting condition and the IP67 rating makes the camera suitable for the harshest environments.

Functions

Active Alarm

The camera features an active alarm to respond automatically to a trigger. The configurable automatic responses include activation of red and blue lights and the broadcast of a built-in message or siren to stop an incident before it happens.

Smart Dual Illuminators

The camera offers both IR and white-light illuminators and intelligently employs each depending on the situation. Typically, the camera enters the IR mode as ambient light decreases. When the camera detects a person entering the monitoring area, it activates the white-light illuminator to capture full-color details. Once the person leaves the area, the camera switches back to IR illumination.

Enhanced Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low light Technology offers best-in-class light sensitivity, capturing details in low light applications. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.



- 1/2.8-in. 8MP Progressive-scan CMOS Sensor
- Triple-stream Encoding
- AI Coding, Smart H.265+, and Smart H.264+ Video Compression
- 8MP (3840 x 2160) at 30 fps, 2.8 mm Fixed Lens
- Analytics+ Functions — Perimeter Protection,
- Smart Motion Detection+
- Two (2) Built-in Microphones and a Built-in Speaker
- Voice Catcher Technology Captures Clear Audio at a Distance
- Dual Smart Illumination — IR and White Light
- Active Alarm with Red/Blue Lights and Siren or Voice Prompt
- Enhanced Starlight Technology for Low-light Applications
- ArcticPro Series Camera — Operational down to -40°C (-40°F)
- IP67 Ingress Protection
- Five-year Warranty*

Smart Motion Detection+

Smart Motion Detection+, a component of Dahua's Analytics+ technology, improves alarm accuracy and decreases the number of false alarms. The advanced SMD algorithm analyzes a scene for human or vehicle motion, while filtering out other motion due to trees, leaves, animals, weather, and triggers an alarm when detected. SMD also saves time when searching recorded video by filtering false alarms and allowing quick retrieval of an alarm due to a person or vehicle.

Perimeter Protection

Dahua Analytics+ includes Tripwire and Intrusion functions that offer custom tripwires based on object type for automation in limited access areas. Perimeter Protection requires less pixels to detect an object to deliver improved accuracy and decreased false alarms due to lights, weather, trees, or animals.

ArcticPro

The Dahua ArcticPro Series of extreme-environment cameras combine temperature-tolerant components, a waterproof enclosure, and an integrated heater to ensure flawless operation in temperatures as low as -40°C (-40°F). For applications that demand high-resolution video with advanced features in extremely cold environments, the Dahua ArcticPro Series offers a camera to satisfy the most demanding requirements.

Cybersecurity

Dahua network cameras are equipped with a series of key cybersecurity technologies including: security authentication and authorization, access control, trusted protection, encrypted transmission, and encrypted storage. These technologies improve the camera's ability to prevent malicious access and to protect data.

Environmental

Subjected to rigorous dust and water immersion tests the camera is suitable for the most demanding outdoor applications. The camera carries an IP67 rating that ensures protection from total dust ingress and protection from water immersion between 15 centimeters and 1 meter in depth.

Technical Specification					
Camera					
Image Sensor		1/2.8-in. 8MP CMOS			
Effective Pixels		3840 (H) x 2160 (V)			
RAM/ROM		128 MB / 512 MB			
Scanning System		Progressive			
Electronic Shutter Speed		Auto, Manual, 1/3 s to 1/100,000 s			
Minimum Illumination		Color: 0.004 lux at F1.0 (30 IRE) B/W: 0.0004 lux at F1.0 (30 IRE) 0 lux at F1.0 (with illuminators on)			
S/N Ratio		Greater than 56 dB			
Illumination Distance		IR: 30.0 m (98.43 ft) White Light: 30.0 m (98.43 ft)			
IR On/Off Control		Auto, Manual			
Illuminators		IR: One (1) LED White Light: One (1) LED			
Lens					
Lens Type		Fixed-focal			
Mount Type		M12			
Focal Length		2.8 mm			
Maximum Aperture		F1.0			
Angle of View		Horizontal: 106° Vertical: 55° Diagonal: 125°			
Iris Type		Fixed			
Close Focus Distance		2.00 m (6.56 ft)			
DORI ¹ Distance	Lens	Detect (8 ppf)	Observe (19 ppf)	Recognize (38 ppf)	Identify (76 ppf)
	2.8 mm	91.0 m (298.56 ft)	36.40 m (119.42 ft)	18.20 m (59.71 ft)	9.10 m (29.86 ft)
Installation Angle					
Range		Pan: 0° to 360° Tilt: 0° to 78° Rotation: 0° to 360°			
Video					
Compression		AI Coding, Smart H.265+, H.265, Smart H.264+, H.264, H.264B, H.264H, MJPEG (sub stream only)			
Streaming Capability		Three (3) Streams			
Resolution		8MP (3840 x 2160), 6MP (3072 x 2048), 5MP (3072 x 1728), 2592 x 1944, 4MP (2688 x 1520), 3MP(2048 x 1536), 2304 x 1296, 1080p (1920 x 1080), 1.3MP (1280 x 960), 720p (1280 x 720), D1 (704 x 480), CIF (352 x 240)			
Frame Rate	Main Stream	8MP (3840 x 2160) at 30 fps			
	Sub Stream 1	D1 (704 x 480) at 30 fps			
	Sub Stream 2	1920 x 1080 at 30 fps			
Bit Rate Control		CBR/VBR			
Bit Rate		H.264: 3 kbps to 20480 kbps H.265: 3 kbps to 20480 kbps			
Day/Night		Auto (ICR), Color, B/W			
BLC Mode		BLC, HLC, True WDR (120 dB), SSA			
White Balance		Auto, Natural, Street Lamp, Outdoor, Manual, Regional Custom			

1.

The DORI distance is a measure of the general proximity for a specific classification to help pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specifications and lab test results according to EN 62676-4, the standard that defines the criteria for the Detect, Observe, Recognize and Identify classifications.


Gain Control		Auto, Manual, Gain Priority, Shutter Priority
Noise Reduction		3D DNR
Motion Detection		Off, On (4 Zones, Rectangular)
Advanced Features		Smart IR, Defog
Image Rotation		0°, 90°, 180°, 270°
Mirror		Off, On
Privacy Masking		Off, On (8 Areas)
Audio		
Input		Two (2) Built-in Microphones
Output		One (1) Built-in Speaker
Compression		PCM, G.711A, G.711Mu, G.726, G.723
Network		
Ethernet		RJ-45 (10/100 Base-T)
Protocol		HTTP, HTTPS, TCP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, IPv4/v6, QoS, UPnP, NTP, ICMP, IGMP, 802.1x
Interoperability		ONVIF Profile S, G, T; CGI, Milestone; P2P
Streaming Method		Unicast / Multicast
Maximum User Access		20 Users (Total Bandwidth: 72 Mbps)
Edge Storage		Network Attached Storage (NAS) SFTP, FTP Micro SD Slot, maximum 256 GB
Web Viewer		IE (Version 8, 9, and 11), Chrome, Firefox
Management Software		DSS, DMSS
Mobile Operating System		iOS, Android
Cybersecurity		Video Encryption, Firmware Encryption, Configuration Encryption, Digest, WSSE, Account Lockout, Security Logs, IP/MAC Filtering, Generating and Importing X.509 Certification, Syslog, HTTPS, 802.1x, Trusted Boot, Trusted Execution, Trusted Upgrade
Certifications		
Safety		UL62368-1 CAN/CSA C22.2 No. 62368-1-14 EN62368-1
Electromagnetic Compatibility (EMC)		CFR 47 FCC Part 15 Subpart B Electromagnetic Compatibility Directive 2014/30/EU
Interface		
Audio	Input	One (1) Channel (RCA), plus two (2) built-in microphones
	Output	One (1) Channel (RCA) plus one (1) built-in speaker
Alarm	Input	One (1) Channel (5 mA, 3 VDC to 5 VDC)
	Output	One (1) Channel (300 mA, 12 VDC)
Electrical		
Power Supply		12 VDC or PoE (IEEE 802.3af, Class 0)
Power Consumption	Basic	12 VDC: 2.9 W PoE: 5.0 W
	Maximum	12 VDC: 7.8 W PoE: 9.6 W
Environmental		
Operating Conditions		−40° C to +60° C (−40° F to +140° F), Less than 95% RH
Storage Conditions		−40° C to +60° C (−40° F to +140° F), Less than 95% RH
Ingress Protection		IP67


Construction	
Casing	Metal
Dimensions	ø110.90 mm x 122.0 mm (4.37 in. x 4.80 in.)
Net Weight	0.745 kg (1.64 lb)
Gross Weight	0.915 kg (2.02 lb)

Analytics+ Functions		
Perimeter Protection with Active Alarm	- Detects human or vehicle violations using the following methods: Tripwire: a target crosses a defined line. Intrusion: a target enters or exits a defined perimeter. - Monitors a combination of detection methods. - Search and retrieve video based on target type. - Configurable automatic response when an alarm is triggered: Red/Blue Light illuminator activation. Siren activation. Includes 11 built-in siren sounds plus ability to record custom recordings.	
	- Differentiates between and classifies human and vehicle objects. - Filters false alarms due to leaves, lights, animals, and other inconsequential objects. - Extracts human or vehicle objects from recorded video for quick target search and retrieval.	
Recommended Detection Distance	Human	Up to 10.0 m (32.81 ft)
	Vehicle	Up to 15.0 m (49.21 ft)

Intelligent Video System Functions	
IVS triggers an alarm and takes a defined action for the following events:	
Standard Features	- Tampering with the camera. - Error writing to an onboard Micro SD card. - Error sending or receiving data over the network. - Unauthorized access to the camera. - IP Address Conflict
Premium Features	
Motion Detection	An object is moving in a designated area.
Scene Change	A person or object moves the camera to change the scene or covers the camera to obscure the scene.

Ordering Information		
Type	Part Number	Description
TiOC Camera	N83BU82	8MP 2.8 mm Eyeball Camera with Analytics+, Active Alarm, Smart Illumination
	PFA106	Mount Adapter
	PFA137	Junction Box
Accessories, optional	PFA130-E	Waterproof Junction Box
	PFA150	Pole Mount (use with PFB305W wall mount)
	PFA151	Corner Mount (use with PFB305W wall mount)
	PFA152-E	Pole Mount (use with DH-PFB205W-E wall mount)
	DH-PFB205W-E	Wall Mount Bracket
	PFA117	Ceiling Mount Extender for PFB220C
	PFB220C	Ceiling Mount (use with PFA106 mount adapter)
	PFB305W	Wall Mount (use with PFA106 mount adapter)
	DH-PFM321D-US	12 VDC, 1 A Power Adapter

Accessories (Optional)		
		
PFA106 Mount Adapter	PFA137 Junction Box	PFA130-E Waterproof Junction Box
		
PFA150 Pole Mount	PFA151 Corner Mount	PFA152-E Pole Mount
		
DH-PFB205W-E Wall Mount Bracket	PFB220C Ceiling Mount	PFA117 Ceiling Mount Extender for PFB220C
		
PFB305W Wall Mount	DH-PFM321D-US 12 VDC, 1 A Power Adapter	

Junction Mount	Wall Mount
PFA137	DH-PFB205W-E
	
Ceiling Mount	Pole Mount
PFA106 + PFB220C	DH-PFB205W-E + PFA152-E
