

# ECD-1100T

## Public Viewer



- Public Viewer
- Maximum Number of Video Devices: 16
- Web Client
- Event trigger, response and notification

## ► Specifications

### Product Profile

Product Type	Video Decoder
Product Application	Video Decoding, Public Viewer
Maximum Resolution	Local: up to 2MP; Remote: up to 12MP
Maximum Number of Cameras	16
Maximum Number of Video Devices	16
Maximum Number of Clients	Local: 1, Remote: 2
Supported Screen Resolution	HDMI: 1080p

### License

License required	No
Free License	16

### Live View

Digital Zoom	Yes
Event Status	Network loss, Motion, DI

### PTZ

PTZ Control	PTZ Control, Speed Control, 32 preset points, 32 preset tours
-------------	---

**Video**

Compression	H.264
Maximum Frame Rate vs. Resolution	30 fps at 1920 x 1080 30 fps at 720 x 480 25 fps at 720 x 576 30 fps at 640 x 480

**Audio**

Audio Type	1-way
------------	-------

**Network**

Network Protocol & Service	TCP, UDP, IP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP
Ethernet Port	1 x RJ-45 connector
Security	Password protected user level

**Event**

Event Trigger	Video loss, Network loss
Event Response	Play alert sound

**System**

Permission control	Multi-group/users, Liveview/setup/remote level permission
Client PC Operating System	Windows 8.1, Windows 7 SP1
Server Operating System	Embedded Linux
USB	1-Port USB 2.0
Language	Multi-Language
System Status Monitor	Real time status reports on remote browser

**Integration**

Unified Solution	Fully compatible with ACTi cameras and encoders
ONVIF Compliant	Yes, Profile S
Web Browser	IE 11 (Please verify that your computer meets the minimum system requirements for Internet Explorer from Microsoft website.)

**Interface**

HDMI Output	1, HDMI Type A
External Storage Interface	USB
Local Access	HDMI monitor, USB keyboard & mouse

**General**

Power Source	DC 12V, PoE Class 3 (IEEE802.3af)
Power Consumption	8.5 W (PoE), 7 W (DC)
Weight	566g (1.25lb)
Dimensions	(W x H x D): 135mm x 114mm x 33mm (5.3" x 4.5" x 1.3")
Bundled Accessories	Power Adapter, Pole Mount
Mount Type	Surface, Pole, VESA mount 10x10
Starting Temperature	-30°C ~ 70°C (-29°F ~ 158°F) in non-isothermal air flows

Operating Temperature	-34°C ~70°C (-29°F ~ 158°F) in non-isothermal air flows
Operating Humidity	10% - 85% RH, non-condensing
Remote Access	Web Client
Approvals	CE, FCC, UL (for bundled power adapter)
Warranty	3 Year(s). For extended warranty offering, see <a href="http://www.acti.com/support/warranty">http://www.acti.com/support/warranty</a>