

ES-855P22C-S7-MI

Lite 5MP Fixed Lens Face Detection Eyeball IP Camera



- 1/2.8" CMOS sensor
- H.265 triple stream encoding
- 3.6mm high-quality optical lens
- 30m IR effective range
- Built-in PoE & Microphone
- An embedded face detection algorithm
- Intelligent video analytics available
- Multiple web browsers supported
- P2P cloud remote viewing by Mobile Application/VMS
- Lightning protection up to 6kV
- IP67 metal casing



System Overview

Lite Series is a super cost-efficient solution that is powered by cutting-edge technology for crystal clear video monitoring with embedded face detection algorithm, the camera supports White/Black list event alarm deployment in different scenarios. The camera also supports multiple industry-leading Intelligent video analytic functions, such as Face Detection for smart event alarms. The P2P cloud function is built-in for every device, allowing more convenient and flexible remote real-time viewing and monitoring.

Functions

H.265

H.265 technology is an evolutionary optimization of the traditional H.264. It includes a series of encoding strategies such as dynamic ROI, smart 2D&3D noise reduction for delivering high-quality videos and greatly saving up to 70% bandwidth and storage.

Protection

With the precise mechanical and rugged metal casing design, IP cameras of the Pro series rated IP67 could stand against water and dust for a long time.

With 10% of input voltage tolerance, the cameras could work safely under extreme or unstable power conditions.

With a working temperature range from -30°C ~ 60°C, the cameras could adapt to a variety of harsh outdoor environments

Technical Parameters

Camera				
Model	ES-855P22C-S7-MI		Flash / DDR	128Mb / 1Gb
Image Sensor	1/2.8" CMOS		IR LED No.	2
Effective Pixels	2560*1920		IR Distance	30m
Min. Illumination	Color: 0.08Lux@F1.6 (AGC ON) B/W:0.001Lux@F1.6 (AGC ON)		S/N Ratio	>52dB
Lens				
Lens Type	Fixed		Aperture	F1.6
Mount Type	Board-in		FOV	85°
Focal Length	3.6mm		Optical Zoom	N/A
Video				
Compression	H.265 / H.264		WDR	DWDR
Resolution	5MP(2560x1920) / 4MP (2688 x 1520) / 3MP (2304 x 1296) / 1080P (1920 x 1080) / 1.3MP (1280 x 960) / 720P (1280 x 720)		Day / Night	Support
Bitrate Control	CBR / VBR		White Balance	Support
Bitrate	H.265: 4Mbps - 16Mbps H.264: 5Mbps - 20Mbps		Defog	Support
Multi-Streaming	Main Stream	5MP@25fps / 4MP@25fps / 3MP@25fps / 1080P@25fps / 960P@25fps / 720P@25fps	Noise Reduction	2D/3D DNR
	Sub Stream	D1@25fps / VGA@25fps / CIF@25fps	Mirror/Flip	Support
	Third Stream	1920X1080@25fps	Corridor Mode	Support
Motion Detection	Support		HLC	Support
Digital Zoom	Support		BLC	Support
Audio Compression	G7.11u		ROI	4 areas
Privacy Mask	5 areas		Anti-flicker	Support
IVA				
Intelligent Video	Face Detection			
Network				
Protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, RTSP, DDNS, NTP, PPPoE, UPnP, SMTP, RTMP		Management Software (VMS)	AntarVis 2.0 ZKBioSecurity IVS ZKBioAccess IVS
Interoperability	ONVIF Profile S, SDK, API		Operation System	Windows
Max. Online Users	3		Mobile APP	AntarView Pro
Web Browser	IE / Firefox / Chrome / Safari		P2P Cloud Service	Support

Interface

Ethernet	1 RJ-45 port (10/100Mbps)	Reset Button	N/A
Audio I/O	Built-in Microphone	Micro-SD Slot	N/A
Alarm I/O	N/A	ANR	N/A
RS485	N/A	USB	N/A

General

Power Supply	PoE(IEEE802.3af), DC 12V±10%	Working Temperature	-30°C to 60°C
Power Consumption	<3W	Working Humidity	10% to 90%
Ingress Protection	IP67	Net Weight	0.30kg
Dimensions (L*W*H)	171 * 75 * 66 (mm)	Gross Weight	0.45kg

Order Information

Camera	Model	Description
5MP Camera	ES-855P22C-S7-MI	5MP Fixed Lens Face Detection Eyeball IP Camera

Dimensions (mm)

