

DC-T4517WRXP 2.8mm

H.265 5MP PoE Extender Bullet Camera



5MP (2592x1944) resolution
IR LED (Distance : 20 m / 65.6 ft)
Fixed-focal lens

PoE, IEEE 802.3at(Class 4), Built-in PoE Extender
Day and night (ICR)
True wide dynamic range (WDR)

Easy installation with DirectIP NVR
H.265 and Intelligent Codec
Supports ONVIF

SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	2.8mm
Aperture	F1.6
Iris Control	Fixed Iris
Angular Field of View	4:3 mode : 80o(H) 56.7o(V) 106.9o(D)16:9 mode : 80o(H) 41.1o(V) 95.4o(D)
Min. Illumination	COLOR : 0.15 lux @ F1.6B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	20 m / 65.6 ft (2 ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot
Image Stabilizer	-
De-fog	Yes
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	-
Network	
Video Compression	Video Motion Detection, Active Tampering Alarm, Trip Zone
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR / VBR, H.264 - CBR / VBR
Audio Compression	-
Two-way Audio	-
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S/T
Max. Frame Rate	4:3 mode : 30ips : 2592 x 1944(WDR)16:9 mode : 30ips : 2592 x 1456(WDR)
Supported Resolution	4:3 : 2592x1944, 1920x1440, 1280x960x 640x48016:9 : 2592x1456, 1920x1080, 1280x720, 640x360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP,RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTp, SMTP, FEN, mDNS, Upnp, SNMPv2
Security	Digest authentication, Password Protection, User access log, IP Filtering, IEEE802.1x(EAP-TLS), Chained Fingerprint, SSL Encryption, HTTPS Encryption
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTSec)	Yes (Up to 60MB)
Edge Storage	-
Alarm and Event	
Trigger Event	Motion Detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio Alarm	-
Audio In / Out	-
Alarm In / Out	-
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP66
Operating Temperature	-20°C ~ +55°C (-4°F ~ +131°F)*Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	PoE IEEE 802.3af (Class 3)
Power Consumption	PoE, IEEE 802.3af (Class 3), 6.5W
Approval	FCC, CE, KC
Mechanical	
Dimensions	70mm X 65mm X 197.5mm (2.76" X 2.56" X 7.78")
Weight	0.4kg (0.88lb)




PRODUCT IMAGE



DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



DA-LM2000

DA-JB2400

DA-RM2000

ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION
DC-T4517WRXP 2.8mm	WALL	 WALL Model: DA-JB2400
	POLE	 POLE Model: DA-LM2000
		 POLE Model: DA-JB2400
	CORNER	 CORNER Model: DA-RM2000
		 CORNER Model: DA-JB2400