

# DC-T4517WRXP 4.3mm

## H.265 5MP PoE Extender Bullet Camera



5MP (2592x1944) resolution  
IR LED (Distance : 20 m / 65.6 ft)  
Fixed-focal lens

PoE, IEEE 802.3at(Class 4)  
Day and night (ICR)  
True wide dynamic range (WDR)

Easy installation with DirectIP NVR  
H.265 and Intelligent Codec  
Built-in PoE Extender

### SPECIFICATIONS

Video	
Image Sensor	1/2.8
Max. Resolution	2592 x 1944
Lens Type	Fixed-focal
Focal Length	4.3mm
Aperture	F1.6
Iris Control	Fixed Iris
Angular Field of View	80o(H) 56.7o(V) 106.9o(D)
Min. Illumination	COLOR : 0.15 lux @ F1.6, B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Day and Night	Yes (ICR)
IR Distance (LEDs)	20 m / 65.6 ft (2 ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Image Stabilizer	-
De-fog	Yes
Video Out	-
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Audio Compression	-
Max. Frame Rate	4:3 mode : 30ips : 2592 x 1944(WDR), 16:9 mode : 30ips : 2592 x 1456(WDR)
Ethernet	1 RJ45 (10/100BASE-T), 1 Additional RJ45 (10/100BASE-T) for PoE Extender
Recording Session Buffer (NLSrec)	Yes (Up to 60MB)
Edge Storage	-
Alarm and Event	
Trigger Event	Motion Detection, Tampering, Trip Zone
Audio In / Out	-
Alarm In / Out	-
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP66
Operating Temperature	-20°C ~ 55°C (-4°F ~ 131°F), Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	PoE, IEEE 802.3at(Class 4)
Power Consumption	PoE, IEEE 802.3at(Class 4), 25.5W, (DC OUT : 42.5-57V=, 0.3A MAX)



### PRODUCT IMAGE



### DIMENSIONS



### ACCESSORIES (OPTIONAL)

Pole Mount	Junction Box	Corner Mount
DA-LM2000	DA-JB2400	DA-RM2000

# ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION
DC-T4517WRXP 4.3mm	WALL	 <span data-bbox="1373 270 1579 314">WALL</span> <span data-bbox="1600 278 1787 305">Model: DA-JB2400</span>
	POLE	 <span data-bbox="1373 365 1579 409">POLE</span> <span data-bbox="1600 373 1793 400">Model: DA-LM2000</span>
		 <span data-bbox="1373 454 1579 498">POLE</span> <span data-bbox="1600 463 1787 489">Model: DA-JB2400</span>
	CORNER	 <span data-bbox="1373 549 1579 593">CORNER</span> <span data-bbox="1600 557 1797 584">Model: DA-RM2000</span>
		 <span data-bbox="1373 638 1579 682">CORNER</span> <span data-bbox="1600 647 1787 673">Model: DA-JB2400</span>