

# DC-T4536HRX

## 5MP IR Bullet Camera with Heater



5MP (2592x1944) resolution  
 Motorized Vari-focal lens (f=3.0 - 13.5mm)  
 micro SD/SDHC/SDXC  
 Two-way audio  
 Alarm in / out

IK10 / IP67 supports  
 Built-in heater  
 Day and night (ICR)  
 True wide dynamic range (WDR)  
 IR LED (Distance : 30 m / 98.4 ft)

3-axis mechanical design for installation  
 PoE (IEEE 802.3af Class 3), 12V DC  
 Easy installation with DirectIP NVR  
 Supports ONVIF

### SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Lens Type	Motorized Vari-focal
Focal Length	3.0 ~ 13.5mm
Aperture	F1.4 ~ F3.2
Iris Control	DC Iris
Angular Field of View	[4:3 mode] Wide : 91o(H) 66o(V) 120o(D) Tele : 31o(H) 23o(V) 38o(D) [16:9 mode] Wide : 91o(H) 49o(V) 107o(D) Tele : 31o(H) 17o(V) 35o(D)
Min. Illumination	COLOR : 0.15 lux @ F2.0 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	30 m / 98.4 ft (6 ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot
Image Stabilizer	-
De-fog	Yes
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	-
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR / VBR, H.264 - CBR / VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S/T
Max. Frame Rate	4:3 mode : 30ips : 2592 x 1944(WDR) 16:9 mode : 30ips : 2592 x 1456(WDR)
Supported Resolution	4:3 : 2592x1944, 1920x1440, 1280x960, 640x480 16:9 : 2592x1456, 1920x1080, 1280x720, 640x360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTp, SMTP, FEN, mDNS, Upnp, SNMPv2
Security	Digest authentication, Password Protection, User access log, IP Filtering, IEEE802.1x(EAP-TLS), Chained Fingerprint, SSL Encryption, HTTPS Encryption
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTSec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Alarm and Event	
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio Alarm	Yes
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP67, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	12VDC, PoE, IEEE 802.3af(Class 3)
Power Consumption	12V-, 1.1A, 13.2W PoE, IEEE 802.3af(Class 3), 11W
Approval	FCC, CE, KC
Mechanical	
Dimensions	80mm X 75mm X 237mm (3.15" x 2.95" x 9.33")
Weight	1.01kg (2.22lb)



### PRODUCT IMAGE















### DIMENSIONS



### ACCESSORIES (OPTIONAL)

Junction Box	Junction Box	Pole Mount	Corner Mount
DA-JB4150	DA-JB2400	DA-LM2000	DA-RM2000

# ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION
DC-T4536HRX	WALL	 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">WALL</span> <span style="margin-left: 10px;">Model: DA-JB4150</span>
		or
	CELLING	 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">WALL</span> <span style="margin-left: 10px;">Model: DA-JB2400</span>
		 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">CEILING</span> <span style="margin-left: 10px;">Model: DA-JB4150</span>
	POLE	or
		 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">CEILING</span> <span style="margin-left: 10px;">Model: DA-JB2400</span>
		 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">POLE</span> <span style="margin-left: 10px;">Model: DA-JB4150</span>
		 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">POLE</span> <span style="margin-left: 10px;">Model: DA-LM2000</span>
	CORNER	or
		 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">POLE</span> <span style="margin-left: 10px;">Model: DA-LM2000</span>
		 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">POLE</span> <span style="margin-left: 10px;">Model: DA-JB2400</span>
		 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">CORNER</span> <span style="margin-left: 10px;">Model: DA-RM2000</span>
	CORNER	+
		 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">CORNER</span> <span style="margin-left: 10px;">Model: DA-JB2400</span>
or		
 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">CORNER</span> <span style="margin-left: 10px;">Model: DA-JB4150</span>		
CORNER	+	
	 <span style="background-color: #00A6C8; color: white; padding: 2px 5px; border-radius: 3px;">CORNER</span> <span style="margin-left: 10px;">Model: DA-RM2000</span>	