

# TC-T5532WRX

## DirectCX 5MP IR Bullet Camera



5MP resolution  
Vari-focal Lens (f=3.0mm ~ 13.5mm)  
Day and night (ICR)

True wide dynamic range (WDR)  
Motion Detection  
De-fog

HLC  
Vandal Proof / IP66 supports  
Coaxial OSD Control

### SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS Sensor
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Frame Rate	TVI : 20ips@5MP, 12.5ips@5MP, 30ips@4MP, 30ips@2MP AHD : 20ips@5MP, 12.5ips@5MP, 30ips@4MP, 30ips@2MP CVBS : NTSC / PAL(for previewing video)
Lens Type	Motorized Vari-focal
Focal Length	3.0mm ~ 13.5mm
Aperture	F1.4 ~ 3.2
Iris Control	DC Iris
Angular Field of View	Wide : 91o(H) 66o(V) 120o(D) Tele : 31o(H) 23o(V) 38(D)
Min. Illumination	COLOR : 0.13 Lux @ F1.4 B/W : 0 Lux (IR LED ON)
S/N Ratio	More than 50dB
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30,1/25Sec ~ 1/30000Sec) / Anti-Flicker
Day and Night	Yes (ICR)
IR Distance (LEDs)	30m / 98.4 ft (4ea)
Video Out	1 HD BNC (Signal Switchable)
Function	
Functions via OSD menu control	<ul style="list-style-type: none"> <li>· AGC : 0 ~ 10 Level Adjustable</li> <li>· Brightness : 0 ~ 20 Level Adjustable</li> <li>· Sens-UP : OFF / x2 ~ x32</li> <li>· WDR(Wide Dynamic Range) : OFF / FRAME / LINE (LOW, MIDDLE, HIGH) ROI Mode Available</li> <li>· Backlight Compensation(BLC) : OFF/ON</li> <li>· HLC : 1 ~ 20 Level Adjustable (ALL DAY/NIGHT ONLY)</li> <li>· ACE(D-WDR/ATR-EX) : OFF / LOW / MIDDLE / HIGH</li> <li>· Motion Detection : OFF/ON (4 Zone)</li> <li>· Privacy Masking : OFF/ON (24 Zone) BOX:16 POLYGON:8</li> <li>· Day &amp; Night : Color/B&amp;W/EXTERN</li> <li>· Smart-IR(IR OPTIMIZER) : 0-20 Level Adjustable</li> <li>· White Balance : AUTO / AUTOext / AWC-SET / MANUAL (3,000K, 5,000K, 8,000K)</li> <li>· Digital Noise Reduction : OFF / LOW / MIDDLE / HIGH</li> <li>· Mirror : MIRROR, FLIP</li> <li>· D-ZOOM(EZOOM) : x1 ~ x16</li> <li>· Sharpness : 0-10 Level Adjustable</li> <li>· De-fog : OFF/ON</li> <li>· GAMMA Correction : r = 0.45 ~ 0.75</li> <li>· Lens Shading(LSC) : OFF / ON(0 ~ 100% Level Adjustable)</li> <li>· Language : ENG / CHN / CHN(S) / JPN / KOR</li> </ul>
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP67
Operating Temperature	-10°C ~ +55°C (14F ~ +131F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	DC 12V, AC 24V
Power Consumption	DC12V/8W, AC 24V/ 8.3W
Mechanical	
Dimensions	80mm x 75mm x 237mm (3.15" x 2.95" x 9.33")
Weight	0.87kg (1.92lb)



### PRODUCT IMAGE















### DIMENSIONS



### ACCESSORIES (OPTIONAL)

Junction Box	Junction Box	Pole Mount	Corner Mount
DA-JB4150	DA-JB2400	DA-LM2000	DA-RM2000

# ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION
TC-T5532WRX	WALL	 <span>WALL</span> Model: DA-JB4150
		or
	WALL	 <span>WALL</span> Model: DA-JB2400
		CEILING
	CELLING	 <span>CEILING</span> Model: DA-JB4150
		or
	CELLING	 <span>CEILING</span> Model: DA-JB2400
		POLE
	POLE	 <span>POLE</span> Model: DA-JB4150
		+
		 <span>POLE</span> Model: DA-LM2000
		or
		 <span>POLE</span> Model: DA-LM2000
		+
	POLE	 <span>POLE</span> Model: DA-JB2400
CORNER		
CORNER	 <span>CORNER</span> Model: DA-RM2000	
	+	
	 <span>CORNER</span> Model: DA-JB2400	
	or	
	 <span>CORNER</span> Model: DA-JB4150	
	+	
 <span>CORNER</span> Model: DA-RM2000		