



## Key Features

- 32 Channel WD1 960x480 recording delivers 36% more detail than traditional 4CIF (704x480)
- H.264 Compression for efficient HDD utilization and streaming
- NTSC/PAL automatic signal selection
- HDMI (720p/1080p) + VGA (to 1920x1080) + BNC main monitors support any type of display
- Call monitor: composite BNC output for quad/sequential/event camera display and PTZ control
- WD1 real-time live display and recording all channels; real time playback on up to 16 channels
- Independent channel setup for resolution/FPS/bitrate/image quality/normal & event record
- Simultaneous high bandwidth recording (480 NTSC/400 PAL @WD1) plus sub-stream recording for reduced bandwidth remote viewing
- Unique Channel 0 remote stream displays user defined multi-view in the bandwidth of a single ch.
- Pentaplex Operation (Simultaneous live, recording, playback, archiving and remote viewing)
- User friendly GUI with graphical icons and visual indicators
  - Easy to use on-screen menus include digital zoom and instant playback of recent video
  - Operate using full front panel controls, wheel mouse or included IR remote
- Quickly locate and review event video
  - Search by date/time, or preview images by pointing along a color coded timeline of record type
  - Tag video of interest for easy retrieval or export
  - Play based on results of extensive event/alarm log search
  - Use "Smart Search" to define an area of interest; the NVR quickly reviews recorded video to list instances of motion in that area for review by the operator
- Watermarking for validation of recorded video
- Easy router setup for remote access: uPnP automatically sets up port forwarding (router must support/allow uPnP)
- Free DDNS Service – static IP address is not required for reliable remote access
- Supports multiple storage options for extended recording;
  - Up to 4 HDD/16Tb internal + eSATA at DVR
  - 8 network disks (8 NAS disks, or 7 NAS disks + 1 IP SAN disk) can be connected.
- Free iOS and Android app:
  - Scroll through single/quad display live views
  - Playback specific cameras by date/time plus easy slider control
  - Audio monitoring support
  - Mobile PTZ control
  - Relay control
  - Up to 16 camera views from HD tablets (HD app)
- Multiple Control Inputs: mouse / front panel / hand held IR remote controller (included)
- Remote configuration support from built-in web interface and/or free CMS program
- Gigabit Ethernet interface for remote network viewing and control
- On-screen PTZ control via mouse or front panel
- External eSATA DVD burner or Optional internal – replaces one HDD
- Audio recording capabilities plus two-way audio support
- USB 2.0 ports on front and rear panels for video archive and mouse usage
- Free Windows CMS displays hundreds of cameras
- Free MAC client software connects to individual sites for live view and playback
- Multi-language support
- Rack mountable; rack ears included



**OMNI960-32**  
32 Channel 960H DVR

# OMNI960

## Scalable 960H Solutions



The KT&C OMNI960-32 brings you the next generation of analog recording. Now you can take full advantage of the 750+ HDTV cameras that give you such precise LIVE views. Now you can RECORD that image detail and deliver the same clarity improvement during PLAYBACK. This WD1/960H technology can record images at a resolution of 960 x 480 pixels (720HDTV), a 36% increase over traditional analog 528HDTV from NTSC 704x480 (4CIF) images. This new application of H.264 compression technology still delivers enhanced recording capacity and improved network image transmission speed, even while it improves image quality. Mix and match 'standard' resolution cameras (up to 540HDTV) with 'improved' (600~700 HDTV) and (720~750+ HDTV) cameras to record as much detail as is available from each one.

This incredibly detailed recording is just the start for the OMNI960-32 DVRs: record up to 30FPS @ full 960H/WD1 resolution – REAL TIME on ALL channels. To help manage LAN/WAN bandwidth for efficient remote monitoring the OMNI960 series implements sub-stream recording. The DVR simultaneously creates and captures both the 960H high resolution image and a second stream at a separately controllable lower resolution and rate that conserves bandwidth for remote display of single or multiple displays of live and playback camera images on a PC, smart phone or tablet via cellular or low bandwidth WAN networks. With sub-stream LIVE and PLAYBACK, it is practical to remotely display multi-camera views at low bandwidth, yet at the click of a mouse the DVR can be directed to supply a fully detailed high resolution image on demand. For extreme bandwidth conservation, the OMNI960 DVRs offer a unique Channel 0 remote stream which displays a user defined multi-view in the bandwidth of a single channel.

Choose the browser you prefer: IE, Chrome, Firefox and Safari are all supported. Go beyond the DVR's web interface: use our free CMS client software on your Windows PC to view and play images from multiple sites. Download the free OMNI Remote app for iOS or Android to scroll through single/quad display live views on your tablet or smart phone (up to 16 live views on HD tablets) or play back specific cameras by date/time with easy slider control. Using internal hard drives of up to 4TB each, the OMNI960-32 DVR can store up to 16TB internally (optional mirroring with multiple drives); in addition, up to 8 network disks (8 NAS disks, or 7 NAS disks + 1 IP SAN disk) and eSATA storage can be connected.

Review recorded video by date and time; by alarm/event; from a bookmark; scan a color coded graphical display of record type (e.g. continuous, motion, event, etc.) versus time to drag the on screen 'time line' to the desired point and immediately begin playback from any time slot. Or, use Smart Search to quickly locate relevant video for review: designate areas of interest and let the DVR scan the recorded video to create an ad-hoc event list when motion is detected in those areas. These fully featured DVRs includes all the control and functional capabilities you expect from high performance platforms: full front panel controls including jog/shuttle, eSATA or USB for export, included IR remote control, full OSD GUI, dual 1080HD main monitors (HDMI and VGA), a BNC main monitor output PLUS a BNC Call monitor, and full web and smart phone/tablet viewer remote operation (including PTZ control).

The OMNI960 Series DVRs come with multiple control inputs. These inputs include USB mouse control, full front panel controls and included IR hand held remote control. Mouse control is combined with a simple Graphical User Interface (GUI), offering experienced PC users the similarity of interactive command to that employed with other computer-controlled devices. With the GUI, users can command specific actions on the OMNI960 Series DVRs through graphical icons and visual indicators. All GUI functions can also be controlled via the front panel keys and IR remote as well.

The OMNI960-32 incorporates a powerful combination of local and remote high resolution monitoring, recording and playback capabilities in a user friendly, easy to operate, familiar DVR system. Get the most out of your 600~750HDTV cameras and experience flexible analog video surveillance with the OMNI960-32.

KT&C America reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

|                               |   |
|-------------------------------|---|
| Video inputs                  | 32-ch   |
| Video input interface         | BNC (1.0 Vp-p, 75 Ω), PAL / NTSC auto detection   |
| Audio input                   | 4-ch, RCA (2.0 Vp-p, 1 kΩ) for recording  |
| Line in                       | 1 RCA for two way audio   |
| Audio compression             | G.711   |
| Two-way audio                 | Audio input pass through to remote web or CMS client; remote audio from web or CMS client pass through to audio output  |
| Encoding resolution           | WD1 / 4CIF / 2CIF / CIF / QCIF  |
| Video compression             | H.264   |
| Dual-stream                   | Supported; Sub-stream: CIF / QCIF @ 25 fps (P) / 30 fps (N)   |
| Stream types                  | Channel 1-4: Video, Video & Audio; Other channels: Video  |
| Frame rate per camera         | 25 fps (P) / 30 fps (N) record Playback up to 16 simultaneous cameras   |
| Video bit rate per camera     | 32 Kbps ~ 3072 Kbps, or user defined (Max. 3072 Kbps)   |
| Recording Modes               | Continuous, Motion, Alarm, Motion + Alarm, Motion or Alarm  |
| Motion Detection              | Configurable per camera for area(s), sensitivity and arming schedule programmable by day of week and hour of day  |
| Schedule Period               | Per day in 1 hour blocks; or 8 time periods per day, each with different record mode; plus holidays   |
| Pre- & Post- Event Recording  | Pre-record 0~30 seconds; post record 5s~10 minutes  |
| Audio compression             | G.711   |
| Audio bit rate                | 64 Kbps   |
| HDMI/VGA output               | 1080P: 1920 x 1080/60Hz; SXGA: 1280 x 1024/60Hz; 720P: 1280 x 720/60Hz; XGA: 1024 x 768/60Hz  |
| CVBS Main Monitor             | 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 x 576, NTSC: 704 x 480   |
| CVBS Spot Monitor             | 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 x 576, NTSC: 704 x 480   |
| Audio output                  | 2-ch, RCA (Linear, 600 Ω) synchronized with CVBS & VGA  |
| Synchronous playback          | 16-ch   |
| Playback search modes         | Time/Date; alarm (motion or log event); Manual Tags; Smart Search for motion events from recorded video   |
| Playback Controls             | Play; Pause; Forward/Reverse; speed control for single~1.8~16X; Slide bar with overview of record type and snapshot display from slider position  |
| Digital Zoom During Playback  | Supported on Local Displays and CMS   |
| SATA                          | 4 SATA interfaces for 2HDDs + 1 DVD-RW (default), or 4 HDDs   |
| Capacity                      | Up to 4TB capacity for each disk  |
| eSATA                         | 1 eSATA interface   |
| NAS/SAN                       | up to 8 network disks (8 NAS disks, or 7 NAS disks + 1 IP SAN disk)   |
| Network interface             | 1, RJ45 10M / 100M / 1000M Ethernet interface   |
| DST/NTP                       | Supported; choice of time zone, NTP server, DST start/end/offset  |
| Port Mapping/uPnP             | Automatic port forwarding/redirection using uPnP on routers with this capability  |
| Serial interface              | 1 RS-232, RS-485(full-duplex), Keyboard   |
| USB interface                 | 3 x USB 2.0   |
| Alarm in                      | 16  |
| Alarm out                     | 8   |
| Built in Web Server Interface | Live view, playback and configuration via IE, Chrome, Firefox, Safari (with free plug-in/extension installed)   |
| CMS                           | PC and MAC Client supports multiple device viewing, playback (with digital zoom) and configuration; user rights per camera; E-map support; live view up to 64 cameras in 4:3 and 48 cameras in 16:9; up to 16 cameras in playback                   |
| Mobile Apps                   | iOS and Android supported; live 1 & 4 camera views; single camera playback; snapshots from live or play; copy clips/record to smartphone; audio support; PTZ control. HD version of app, optimized for tablets, displays up to 16 live view cameras |
| User Rights Control           | Per user-per camera for multiple functions  |
| Event Logging                 | Multiple types: alarm, exception, operation, information; dozens of sub-types within each major type  |
| Firmware Upgrade              | From USB or remotely  |
| Backup/Restore Config         | From USB or remotely  |
| Power supply                  | 100~240VAC, 5A, 50~60Hz   |
| Consumption                   | ≤ 40 W (without HDD or DVD-RW)  |
| Operating Temperature         | -10 °C ~ +55 °C   |
| Operating Humidity Range      | 10% ~ 90%   |
| Chassis Type                  | 19-inch rack-mountable 1.5U chassis; rack ears included   |
| Dimensions (W x D x H)        | 17.52" x 15.35" x 2.76"   445 x 390 x 70 mm   |
| Weight                        | ≤ 11 lbs.   ≤ 5 kg (without HDD or DVD-RW)  |

### Ordering Information:

[www.ktncusa.com](http://www.ktncusa.com)

OMNI960-32/2TB: 32 Ch, 2 TB | OMNI960-32/4TB: 32 Ch, 4 TB | OMNI960-32/8TB: 32 Ch, 8 TB

OMNI960-32/12TB: 32 Ch, 12 TB | OMNI960-32/16TB: 32 Ch, 16 TB