

PMAX-0114



Mount Kit for Dome Cameras (for A8x, except A88)

► Specifications

Device


Product Type	Camera Mount
Application Environment	Indoor/Outdoor
Description	Mount Kit for Dome Cameras (for A8x, except A88)







General

Weight	580g (1.28lb)
Dimensions	(Ø x H): 152mm x 74mm (5.99" x 2.92")
Color	White
Material	Aluminum
Warranty	1 Year(s)

► Related Products

Dome - Zoom Dome

A81		3MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8 (HOV:90.6°-32.7°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO
-----	---	--

A815		3MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8 (HOV:90.6°-32.7°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO
A82		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 2.8x Zoom lens, f3.6-10mm/F1.5-2.8 (HOV:79.5°-38.1°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO
A83		2MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8 (HOV:88°-25°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO
A85		2MP Video Analytics Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO, Built-in Analytics
A86		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO
A87		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Advanced WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8 (HOV:71°-25°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO