

PMAX-0210



POE Stainless Steel Housing with Heater, Fan and Bracket


► Specifications

Device

| | |
|--------------|--|
| Product Type | Box Camera Housing |
| Description | POE Stainless Steel Housing with Heater, Fan and Bracket |




General

| | |
|----------------------|--|
| Power Source | High PoE (IEEE802.3at) |
| Power Consumption | High PoE: Max. 25.5W (camera and housing with heater and fan on) |
| Weight | 9000g (19.842lb) |
| Dimensions | (Ø x L): 132mm x 400mm (5.20" x 15.75") |
| Environmental Casing | Weatherproof (IP68) |
| Fan | Yes, 40°C / 104°F (fan on), 30°C / 86°F (fan off) |
| Heater | Yes, 15°C / 59°F (heater on), 24°C / 77°F (heater off) |
| Approvals | IP68, NEMA 250-2014 Type 4X |
| Color | Silver |
| Material | Stainless Steel 316 |
| Warranty | 1 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty |





▶ Related Products


Box - Box

| | | |
|------|---|--|
| A213 |  | 5MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F2.0, Auto Back Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, MicroSDHC/ MicroSDXC, PoE/DC12V, DI/DO, RS-485 |
| A29 |  | 2MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F1.8 (HOV:108.6°), Auto Back Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, RS-485 |
| E217 |  | 2MP Video Analytics Box with D/N, Extreme WDR, SLLS, Fixed lens, f2.93mm/F2.0 (HOV:101.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics |

Box - Zoom Box

| | | |
|-----|---|--|
| B26 |  | 3MP Video Analytics Zoom Box with D/N, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics |
| I29 |  | 2MP Video Analytics Zoom Box with D/N, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics |

Network & Storage Peripherals - Data Switch

| | | |
|-----------|---|---|
| PPSW-0105 |  | PLANET GS-4210-8P2C 8-Port Gigabit 802.3at Managed PoE Switch (PoE Budget 120W) |
|-----------|---|---|

