

# PMAX-0312



PTZ Wall Mount for Outdoor PTZ / Speed Dome  
(except KCM-8211 & TCM-6630)

## ► Specifications

### Device


Product Type	Camera Mount
Description	PTZ Wall Mount for Outdoor PTZ / Speed Dome (except KCM-8211 & TCM-6630)

### General






Weight	827.5g (1.82lb)
Dimensions	(W x H x D): 90mm x 140mm x 175mm (3.54" x 5.51" x 6.89")
Color	Warm Gray
Material	Aluminum
Warranty	1 Year(s)

## ► Related Products

### PTZ - Speed Dome

B915	 <p>3MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics</p>
------	---



B916		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 20x Zoom lens, f4.7-94mm/F1.6-3.5 (HOV:62°-2.8°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
B928		5MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:51.14°-2.17°), DC iris, Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I915		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I96		2MP Outdoor Speed Dome with D/N, Extreme WDR, ELLS, 30x Zoom lens, f4.3-129mm/F1.6-5.0 (HOV:66.4°-2.61°), DC iris, Auto Focus, H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO
I98		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:69.3°-3°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics

