

# PMAX-0316

Wall Mount (for D5x, D9x, E5x, E9x, E9xx/M)



## ► Specifications

### Device


Product Type	Camera Mount
Application Environment	Indoor
Description	Wall Mount (for D5x, D9x, E5x, E9x, E9xx/M)






### General

Weight	278.5g (0.61lb)
Dimensions	(W x H x D): 140.5mm x 121mm x 55.5mm (5.53" x 4.76" x 2.19")
Color	Warm Gray
Material	Aluminum
Warranty	1 Year(s)



## ► Related Products

### Dome - Mini Dome

E93		5MP Indoor Mini Dome with Basic WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.9° (overview area), 77.4° (high detail area)), H.264, 1080p/30fps, DNR, MicroSDHC/MicroSDXC, PoE, IK08
-----	---	--

E97		10MP Indoor Mini Dome with Basic WDR, Fixed lens, f3.6mm/F1.8 (HOV:101.4°), H.264, 1080p/30fps, DNR, MicroSDHC/MicroSDXC, PoE, IK08
E918		3MP Outdoor Mini Dome with Superior WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.4° (overview area), 77.1° (high detail area)), H.264, 1080p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP68, IK10, EN50155
E933		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP68, IK10, EN50155, Built-in Analytics
E933M		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, M12 connector, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP68, IK10, EN50155, Built-in Analytics
E936		2MP Video Analytics Outdoor Mini Dome with Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP68, IK10, EN50155, Built-in Analytics

**Dome - Mini Fisheye Dome**

E96		5MP Indoor Mini Fisheye Dome with Basic WDR, Fixed lens, f1.19mm/F2.0 (HOV:189.7° (overview area), 115.7° (high detail area)), H.264, DNR, MicroSDHC/MicroSDXC, PoE, IK08
E925		5MP Outdoor Mini Fisheye Dome with D/N, Adaptive IR, Basic WDR, Fixed lens, f1.19mm/F2.0 (HOV:189.7° (overview area), 115.7° (high detail area)), H.264, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP68, IK10, EN50155

