

PMAX-0505



Pole Mount (for B4x, B41x, E44, E45, E46, E48, E44A, E45A, E46A, E41x, I4x, PMAX-0312, PMAX-0313, PMAX-0314, PMAX-0330) , supports 2" to 3" Poles

► Specifications

Device


| | |
|-------------------------|---|
| Product Type | Camera Mount |
| Application Environment | Indoor/Outdoor |
| Description | Pole Mount (for B4x, B41x, E44, E45, E46, E48, E44A, E45A, E46A, E41x, I4x, PMAX-0312, PMAX-0313, PMAX-0314, PMAX-0330) , supports 2" to 3" Poles |

General






| | |
|----------------------|---|
| Supported Pole Range | 2" ~ 3" |
| Weight | 450.5g (0.993lb) |
| Dimensions | (W x H x D): 137.3mm x 150mm x 120mm (5.4" x 5.9" x 4.7") |
| Color | Warm Gray |
| Material | Aluminum |
| Warranty | 1 Year(s) |

► Related Products






Bullet - Bullet

| | | |
|-----|---|--|
| E46 |  | 3MP Bullet with D/N, Adaptive IR, Superior WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:70.5°-28.8°), H.264, 1080p/30fps, DNR, PoE, IP68, IK10 (metal casing) |
|-----|---|--|

Bullet - Zoom Bullet

| | | |
|------|---|--|
| B412 |  | 3MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:58°-5.8°), DC iris, Auto Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics |
| B419 |  | 5MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics |
| B44 |  | 1.3MP Zoom Bullet with D/N, Adaptive IR, Basic WDR, SLLS, 10x Zoom lens, f4.9-49mm/F1.6-3.0 (HOV:52.1°-5.7°), DC iris, Auto Focus, H.264, 720p/60fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP67, IK10 (metal casing), DI/DO |
| E417 |  | 2MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.9-49mm/F2.8-3.5 (HOV:60°-7.3°), Adaptive iris, Auto Focus (for installation), H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10 (metal casing), DI/DO, Built-in Analytics |
| I42 |  | 2MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics |

Dome - Zoom Dome

| | | |
|------|---|--|
| A811 |  | 4MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:104°-29°), Auto Focus (for installation), H.265/H.264, 1080p/30fps, , 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10, DI/DO |
| A818 |  | 6MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:82.2°-28.7°), Auto Focus (for installation), H.265/H.264, 1440p/30fps, 3D DNR, Audio, MicroSD/MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10, DI/DO |
| A820 |  | 4MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:102.8°-32.4°), H.265/H.264, 3D DNR, Audio, MicroSD/MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10, DI/DO |
| A821 |  | 6MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:102.1°-34.5°), H.265/H.264, 3D DNR, Audio, MicroSD/MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10, DI/DO |
| Z83 |  | 2MP Outdoor Zoom Dome with D/N, Adaptive IR, Superior WDR, SLLS, 4.3x Zoom lens, f2.8-12mm (HOV:112.7°-28.1°), Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, MicroSDHC/MicroSDXC, PoE/DC12V, IP67, IK10 |

Z84



4MP Outdoor Zoom Dome with D/N, Adaptive IR, Superior WDR, SLLS, 4.3x Zoom lens, f2.8-12mm (HOV:91°-27°), Auto Focus (for installation), H.265/H.264, 2D+3D DNR, MicroSDHC/MicroSDXC, PoE/DC12V, IP67, IK10

