



PMH-POE08130WAT

8 PORT POE FAST ETHERNET SWITCH



FEATURES :

- 8 Port 10/100M (Auto-negotiation) Switch
- 8 PSE/PoE function ports
- Supporting the power Max. 15.4 W for each PSE/PoE port
- 11" Desktop size with metal case
- Can be installed in a 19" cabinet by rack-mount kits
- Auto-learn of networking configurations
- Auto-detect full/half-duplex modes for any port
- Dedicated full-duplex 200Mbps bandwidth
- Store-and-Forward switching methods
- IEEE 802.3x flow control for full-duplex and back-pressure flow control for half-duplex
- Non-blocking & Non-head-of-line blocking full wire speed forwarding
- Auto-MDI/MDI-X function for any port / Smart plug & play

SPECIFICATION :

Standards	IEEE 802.3af / IEEE 802.3 10BaseT / IEEE 802.3u 100BaseTX / IEEE 802.3x Flow control
Filtering/Forwarding Rates	100Mbps port - 148,800pps 10Mbps - 14,880pps"
Transmission Media	10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP"
LED Indicators	Per Port: LINK/ACT, PoE ACT/Status Per Unit: Power"
Power Input	100 - 240V/AC, 50 - 60Hz
Power Output	48V/DC Per Port Output -15.4 W Max Per Port 8 Ports at Full 15.4 W Output Supported
Power Consumption	130 Watts (Max)
Dimensions	266 x 160 x 44 mm (L x W x H)
Weight	1.6 kg
Operating Temperature	0 to 55°C
Storage Temperature	-20 to 90°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class A, CE

DIMENSIONS : (Unit : mm)

266 x 160 x 44

