

PMIC-0200



- Passive Microphone
- Condenser Type
- Omni-Directional

► Specifications

Device

Product Type	Microphone
Description	Passive Microphone Omnidirectional for all Cameras with Mic-in Audio using 3.5mm Phone Jack, no extra DC power needed

Audio

Microphone Type	Passive
Transducer Type	Condenser
Frequency Response	50 - 20000 Hz
Impedance	2200 ohms
Audio Sensitivity	-34 +/- 3 dB
SNR	58 dB
Operating Voltage	Standard 2V; Max. 5V
Current Consumption	Max. 0.5mA
Polar Pattern	Omni-Directional

Interface

Audio Interface	3.5mm Phone Jack
-----------------	------------------








General

Power Source	no extra DC power needed
--------------	--------------------------

Weight	25g (0.055lb)
Bundled Accessories	Surface mount
Cable Length	2 m
Warranty	1 Year(s)

► Related Products

Bullet - Zoom Bullet


A415		3MP Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8 (HOV:88°-25°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10 (metal casing), DI/DO
A421		8MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.3, Auto Focus (for installation), H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
A425		2MP Zoom Bullet with D/N, Adaptive IR, Extreme WDR, ELLS, 4.3x Zoom lens, f2.8-12mm/F1.8-3.3 (HOV:106.6°-34.6°), Adaptive iris, Auto Focus (for installation), H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP67, IK10 (metal casing), DI/DO
A46		5MP Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10 (metal casing), DI/DO
B412		3MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:58°-5.8°), DC iris, Auto Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
B419		5MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
E417		2MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.9-49mm/F2.8-3.5 (HOV:60°-7.3°), Adaptive iris, Auto Focus (for installation), H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10 (metal casing), DI/DO, Built-in Analytics

Dome - Mini Dome



E918		3MP Outdoor Mini Dome with Superior WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.4° (overview area), 77.1° (high detail area)), H.264, 1080p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP68, IK10, EN50155
E933		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP68, IK10, EN50155, Built-in Analytics

E933M		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, M12 connector, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP68, IK10, EN50155, Built-in Analytics
E936		2MP Video Analytics Outdoor Mini Dome with Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP68, IK10, EN50155, Built-in Analytics





Dome - Mini Fisheye Dome

E925		5MP Outdoor Mini Fisheye Dome with D/N, Adaptive IR, Basic WDR, Fixed lens, f1.19mm/F2.0 (HOV:189.7° (overview area), 115.7° (high detail area)), H.264, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE, IP68, IK10, EN50155
------	-----------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dome - Hemispheric Dome

B511A		12MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, Built-in Analytics
B57		6MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.3mm/F2.6 (HOV:187°), H.264, Dewarping, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, Built-in Analytics

PTZ - Speed Dome

B913		5MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:49.1°-2.23°), DC iris, Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/DC12V, IK09, DI/DO, Built-in Analytics
B923		3MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:58.5°-3.2°), DC iris, Auto Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/DC12V, IK09, DI/DO, Built-in Analytics
B934		2MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:62.4°-3.5°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/DC 12V, IK09, DI/DO, Built-in Analytics
B916		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 20x Zoom lens, f4.7-94mm/F1.6-3.5 (HOV:62°-2.8°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics