








Comparison Chart for PN300, PN400, and PN401

Model	PN300		PN400	PN401
				
Video Format	Multimedia Support		Multimedia Support	Multimedia Support
Audio Format	G.711		Multimedia Support	Multimedia Support
Photo Format	PNG / JPEG / BMP		PNG / JPEG / BMP	PNG / JPEG / BMP
Audio Output	HDMI / 3.5 mm jack		HDMI	HDMI / 3.5 mm jack
Video Output	HDMI	VGA	HDMI	HDMI
	480p	640 x 480	1920 x 1080 at 30 Hz	1920 x 1080 at 30 Hz
	720p	1024 x 768	1920 x 1080 at 60 Hz	1920 x 1080 at 60 Hz
	1080i	1280 x 768	3840 x 2160 at 24 Hz	3840 x 2160 at 24 Hz
	1080p	1366 x 768	3840 x 2160 at 30 Hz	3840 x 2160 at 30 Hz
Video Input	N/A		HDMI, 1920 x 1080 at 30 Hz	N/A
TV Standard	NTSC / PAL		NTSC / PAL	NTSC / PAL
SD/SDHC card	Class 4 or above (FAT32 and NTFS formats)		Class 6 or above (FAT32 and NTFS formats)	Class 4 or above (FAT32 and NTFS formats)
USB	USB 2.0 backward compatible (FAT32 and NTFS formats)		USB 2.0 backward compatible x 2 USB 3.0 backward compatible x 1 (FAT32 and NTFS formats)	
IR Remote Control	Yes		Yes	Yes
USB Mouse Control	N/A		Yes	Yes
Power Adapter	12V / 3A DC Jack (Max. 36 W)		12V / 3A DC Jack (Max. 36 W)	12V / 3A DC (Max. 36 W) / PoE 802.3af
Operating Temperature	0 °C ~ 40 °C / 32 °F ~ 104 °F		5°C ~ 40 °C / 41 °F ~ 104 °F	0°C ~ 40°C / 32 °F ~ 104 °F
Operating Humidity	20 % ~ 80 % (with no condensation)		20 % ~ 80 % (with no condensation)	20 % ~ 80 % (with no condensation)
Dimensions (W x H x D)	182.5 × 29 × 141.5 mm / 7.19 × 1.14 × 5.58 in		173 × 34.2 × 117.6 mm / 6.81 × 1.35 × 4.63 in	152 × 34 × 102 mm / 6 × 1.35 × 4.04 in
Net Weight	615 g / 1.36 lb		615 g / 1.36 lb	500 g / 1.10 lb
Language	English / French / German / Italian / Japanese / Portuguese / Russian / Spanish / Traditional Chinese		English / French / German / Italian / Japanese / Portuguese / Russian / Spanish / Traditional Chinese	English / French / German / Italian / Japanese / Portuguese / Russian / Spanish / Traditional Chinese / Polski



Comparison Chart for SQP110 Series and SQP133

Model	SQP110 series	SQP133
		
Video Format	Multimedia Support	Multimedia Support
Audio Format	Multimedia Support	Multimedia Support
Photo Format	PNG / JPEG	PNG / JPEG / BMP
Audio Output	Built-in speaker (2 W x 2)	Built-in speaker (4 ohm / 1.5 W)
Video Output	800 x 600	1280 x 800
Video Input	N/A	N/A
TV Standard	NTSC / PAL	NTSC / PAL
SD/SDHC card	Class 4 or above (FAT32 and NTFS formats)	Class 4 or above (FAT32 and NTFS formats)
USB	USB 2.0 backward compatible (FAT32 and NTFS formats)	USB 2.0 backward compatible (FAT32 and NTFS formats)
IR Remote Control	Yes	Yes
USB Mouse Control	N/A	Yes
Power Adapter	12V / 3A DC Jack (Max. 36 W)	12V / 3A DC Jack (Max. 36 W)
Operating Temperature	0 °C ~ 40 °C / 32 °F ~ 104 °F	0 °C ~ 40 °C / 32 °F ~ 104 °F
Operating Humidity	20 % ~ 80 % (with no condensation)	20 % ~ 80 % (with no condensation)
Dimensions (W x H x D)	292 x 186 x 46 mm / 11.5 x 7.3 x 1.8 in	342.8 x 220.3 x 38.3 mm / 13.5 x 8.7 x 1.5 in
Net Weight	1.5 kg / 3.3 lb	1160 g / 2.6 lb
Language	English	English / French / German / Italian / Japanese / Portuguese / Russian / Spanish / Traditional Chinese