

PPOE-0201



High PoE injector Single-port, IEEE 802.3bt Type 4, Gbps, 90W 4-Pairs POE indoor midspans, AC 100~240V, with universal connectors (for Z953, Z954, Q83, Q84)

► Specifications

Device

Product Type	PoE Injector
Description	High PoE injector Single-port, IEEE 802.3bt Type 4, Gbps, 90W 4-Pairs POE indoor midspans, AC 100~240V, with universal connectors (for Z953, Z954, Q83, Q84)

Network



Ethernet Port	PoE: 1 port(s), Ethernet (10/100/1000 Base-T), RJ-45 connector
---------------	--

General


PoE Standard	IEEE 802.3bt
PoE Output	Maximum 90 Watts (4-pair)
PoE Power Budget	Maximum 90 W
Power Source	AC 100-240V
Weight	475g (1.05lb)
Dimensions	(L x W x H):166.4mm x 88.7mm x 43.9mm (6.55" x 3.49" x 1.73")
Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F)
Approvals	FCC, VCCI
Warranty	1 Year(s)

▶ Related Products

PTZ - Speed Dome

Z953		8MP Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 40x Zoom lens, f5.7-228mm/F1.2-4.6 (HOV: 61.4°-2.15°), Auto Focus, H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, High PoE/DC24V/AC24V, IP66, DI/DO
Z954		8MP Outdoor Speed Dome with D/N, Adaptive IR, Superior WDR, SLLS, 25x Zoom lens, f6-150mm/F1.5-3.4 (HOV: 60.5°-3.1°), Auto Focus, H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, MicroSD, High PoE/DC24V/AC24V, IP66, DI/DO

Multi-Imager - Multi-Imager 360 Degree Dome

Q84		20MP Outdoor Multi-Imager 360 Degree Dome with D/N, IR, four Zoom lenses, f2.7-13.5mm/F1.2 (HOV:110.3°-31°), H.265/H.264, 2D+3D DNR, Built-in Microphone, High PoE/DC24V/AC24V, IP67, IK10, DI/DO
-----	---	---

