






Comparison of GV-PoE Adapters

	GV-PA191	GV-PA482	GV-PA901	GV-PA902BT	GV-PA903BT
Models					
Features					
PoE Standard	Power over Ethernet (Max. 19 W)	High Power Over Ethernet (Max. 120 W)	High Power Over Ethernet (Max. 90 W)	Gigabit High Power Over Ethernet (Max. 95 W)	Gigabit High Power Over Ethernet (Max. 95 W)
PoE Output (10/100 Mbps)	DC 48V, 400 mA (Max. 19 W)	DC 48V, 2.5A (Max. 120 W)	DC 56V, 1.6A (Max. 90 W)	DC 54V (Max. 95 W)	
PoE Output (10/100/1000 Mbps)	N/A				
Ethernet Cable Length	Max 100 m / 328 ft from Hub to IP device, CAT5		Max 100 m / 328 ft from Hub to IP device, CAT5e	Max 100 m / 328 ft from Hub to IP device, CAT5e, 6	
Power Input	DC 48V, 400 mA	AC 100V ~ 240V, 2.5A	AC 100V ~ 240V, 2A	AC 100V ~ 240V	
Dimensions (L x W x H)	43 x 69 x 40 mm (1.69 x 2.72 x 1.57 in)		69 x 40 x 93 mm (2.72 x 1.57 x 3.66 in)	170 x 102 x 40 mm (6.69" x 4.01" x 1.57")	170 x 100 x 40 mm (6.69" x 3.94" x 1.57")
Weight	130 g (0.29 lb)		250 g (0.55 lb)	0.95 kg (2.09 lb)	0.76 kg (1.68 lb)
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)			0°C ~ 40 °C (32 °F ~ 104°F)	
Surge Protection	N/A			±6 kV	±4 kV
Applied to	<ul style="list-style-type: none"> General GV-IP Cameras with PoE support and a power consumption of less than or equal to 19 W 	<ul style="list-style-type: none"> GV-BX4700-E GV-LPC1100 / 2210 	<ul style="list-style-type: none"> GV-PPTZ7300 / 14021 / 14031 GV-SD2301 V2 / 2411 V2 / 2723-IR / 2733-IR GV-SV48000 	<ul style="list-style-type: none"> GV-LPR2800-DL GV-PPTZ7300 / 14021 / 14031 GV-QSD5731-IR GV-SD2301 V2 / 2411 V2 / 2723-IR / 2733-IR GV-SV48000 	