



Single-port Thunderbolt 3 to single-port 10GbE NBASE-T RJ-45

Network Adapters	Thunderbolt to 10GbE
PHY IC	AQC107S
I/O	1 x Thunderbolt 3, 1 x 10GbE/NBASE-T connector
Transmission rates	10Gbps/5Gbps/2.5Gbps/1Gbps/100Mbps
Operating temperature	5 - 45 °C (23 - 113°F)
Package Contents	QNA-T310G1T, 0.5M Thunderbolt 3 cable and manual
Port and cable	RJ-45; Cat 6a cable recommended
Note	<ul style="list-style-type: none"> ● Windows® devices: The driver for the Marvell AQtion AQC107 is required to use the QNA-T310G1T. Click here to download drivers ● Mac devices: Requires macOS 10.13.3 (or later). ● Linux: Supports Linux core 3.10, 3.12, 3.2, 4.2, and 4.4. The driver for the Marvell AQtion AQC107 is required to use the QNA-T310G1T. Click here to download drivers ● QNAP Thunderbolt™ 3 NAS: Requires QTS 4.3.6 (or later).

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.