



USB 3.2 Gen 1 to 5GbE Adapter

Network Adapters	USB to 5GbE
PHY IC	AQC111U
I/O	1 x USB 3.2 Gen 1 Type-C; 1 x 5GbE/NBASE-T port
Transmission rates	5Gbps/2.5Gbps/1Gbps/100Mbps
Operating temperature	5 - 45 °C (23 - 113°F)
Package Contents	QNA- UC5G1T; 0.2M USB 3.2 Gen 1 Type-C to Type-A cable and installation guide
Port and cable	RJ-45
Note	<ul style="list-style-type: none"> ● Windows 10, 8.1, 8, 7 requires a driver. Requires the Marvell® AQtion AQC111U driver. Click here to download the driver. ● QNAP NAS: QTS 4.3.6 (or later) is required. ● QNAP has ended official support for MacOS and Linux since 2021/01. Users can download the Marvell® AQtion AQC111U driver from Marvell®' s official website. Click here to download the driver. ● Windows 11 and future versions are not supported.

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.