



## USB 3.2 Gen 2 dual-port PCIe expansion card

Connectors	2 x USB Type-A
USB Host controller	ASMedia ASM3142
PCIe and Lanes	PCIe Gen2 x 2
Bracket	Low-profile pre-installed. Low-profile and Full-height are included.
Form Factor	Low-profile 89.65 x 68.9 x 14 mm (Without bracket)
Working Temperature	0 ~ 40 °C (32 ~ 104°F)
Working Humidity	5 ~ 95% RH
Supported Operating System	QTS 4.3.6 (or later) QuTS hero Windows 8.x/10 (32/64-bit) Ubuntu 20.04 LTS
Package Contents	1 x USB expansion card; 1 x QIG; 2 x Brackets

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.