

R71CF-31

2MP



- Access Control with Card + Face Recognition (99%)
- 5" LCD Color Touch Screen
- Wiegand Reader and Controller
- Bundle with 3000 Face Database
- Built-in MIFARE Card Reading Module
- Not available in the USA

► Specifications

Device

Product Type	Reader and Controller
Device Type	Access Controller RFID Reader Face Reader
Maximum Resolution	2MP
Product Application	Access Control with Card + Face Recognition (99%)
Description	2MP Mifare LCD Card Face Recognition Wiegand Wireless Reader and Controller with Bundle 5,000 Card Database / 3,000 Face Database, Door Bell Button, Networking
LCD Screen	5" Color Touch Screen; Resolution: 480 x 800

Lens

Focal Length	Fixed focal
--------------	-------------

Video

Built-in Analytics	Face Recognition, RFID Recognition
--------------------	------------------------------------

Network

Ethernet Port	Non-PoE: 1 port(s), Ethernet (10/100 Base-T), RJ-45 connector
---------------	---

Video Analytics

Analysis Source Type	Video, Image
Metadata Accuracy	Excellent
Face Recognition Distance	0.3m - 1m

Event

Event Log	100,000
-----------	---------

System

Operating System	Linux
------------------	-------

Access Control Functionality

Access Mode	Card only, Face only, Card and Face
-------------	-------------------------------------

RFID Card

Communication Frequency	13.56 MHz
RFID Standard	ISO 14443A
RFID Options	MIFARE

Storage

User Database	Card Capacity: 5000 Face Picture Capacity: 3000
Face Only Detection User Limit	3000

Interface

Serial Port	1 x RS-485
Wireless	Wi-Fi (IEEE 802.11b/g/n)
Digital Input/Output	2/1

General

Power Source	DC 12V (adapter not included), 2 A
Weight	919g (2.026lb)
Dimensions	(W x H x D): 281.5mm x 113mm x 45mm (11.08" x 4.45" x 1.77")
Environmental Casing	Weather resistant (IP65)
Operating Temperature	-20°C ~ 50°C (-4°F ~ 122°F)
Operating Humidity	10% - 90% RH
Approvals	CE, FCC
Color	Silver
Warranty	1 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty

▶ Related Products**Power Supply Accessories - Power Adapter**

PPBX-0015		Power Adapter AC 100~240V (12V/2A Output), with universal connectors for R21CF-xx
-----------	---	---