

SF1008-WP Outdoor & Vandal Resistant Face Recognition Terminal

SpeedFace model SF1008-WP is a high-performance outdoor face & palm recognition reader used primarily in access control applications. It combines a powerful embedded camera and ZKTeco's latest face & palm recognition algorithm supported by an optimized dual-core processor. SF1008-WP is unmatched in accuracy, speed and versatility. Advanced security and convenience, all on a single affordable platform.

By combining the latest advancements in artificial intelligence with an optimized dual-core CPU, SF1008-WP has truly reached a new height in user authentication technology. It's powerful embedded anti-spoofing engine can withstand almost all types of fake photo attacks.

SF1008-WP can store and match up to 50,000 faces in less than 0.3 seconds per face in both extreme lighting (>50,000 lux) and severe rain conditions. It's IP68 and IK04 rating ensures its reliable operation even in the most hostile environments.

It's 3-in-1 (Palm Shape/Print/Vein) recognition is performed in 0.35 seconds and stores up to 5,000 templates. SF1008-WP is truly the ultimate in secure, convenient, and reliable hands-free user authentication for numerous applications.



SPECIFICATIONS:

Capacity

Faces: 50,000 (1:N)
Palms: 5,000 (1:N)
Users/Cards: 50,000
Transactions: 1,000,000
User Photos: 30,000
Event Photos: 10,000

Compatibility

Security Relay Box
Wiegand / RS485 / RS232 Secondary
Reader with Fingerprint / RFID / Bar
code / QR-Code ZKBioSecurity
Software

Hardware

900MHz Dual Core Customized AI CPU
512 MB RAM / 8G Flash
8" Bright Light (400lux) IPS Touch LCD
125KHz EM Reader/ 13.56MHz MF
(optional)
Adjustable Light Brightness LED
Hi-Fi Voice
Receiver Sensitivity Microphone
Distance detection Sensor
Reset Button and Tamper Switch

Access Control Interface

Lock Relay Output
Alarm Output / Auxiliary Input
Exit Button / Door Sensor

Special Functions

IIP68& IK04
0.3s High Speed Facial Verification
on
Live Face Detection
Event Snapshot
Communication Https Encrypted
(optional)

Standard Functions

Access Levels, Groups, Holidays,
DST, Duress Mode (password),
Anti-Passback, Record Query,
Custom Wallpaper & Screen
Saver, Tamper Switch Alarm

Communication

TCP / IP
Wiegand Input / Output
Wi-Fi (optional)
RS485 / RS232


Additional Info

Face Algorithm: ZKLiveFace
5.8
Working Temp.: -22 F to 140 F
Working Humidity: < 93%
Storage Temp: -40 F to 149 F
Storage Humidity: < 93%
Net Weight: 1.88 lbs
Dimension (HLD): 8.9 x 5.6 x 1
inches


Power

Operating Voltage 12V DC
Current Draw < 2,000mA


CONFIGURATION:



DIMENSIONS (IN):



SF1008-WP ADJUSTABLE STAND:




Dimensions (LxWxB): 66.9 x 13.7 x 10.2 inches

Metal: Mild Steel

Coating: Powder coat

Color: Black Default

DIMENSIONS (IN):



ZKTeco USA

1600 Union Hill Rd., Alpharetta GA 30005

Phone: (862) 505 - 2101 • Fax: (862) 204 - 5906 • sales@zkt.ecousa.com • www.zkt.ecousa.com

© Copyright 2019. ZK Teco Inc. ZKTeco Logo and ZK Teco USA Logo have registered trademarks of ZK Teco or a related company.

All other product and company names mentioned are used for identification purposes only and may be trademarks of their respective owners.

All specifications are subject to change without notice. All rights reserved.