



V Series

IB9367-EHT-V2 (5-50 mm)

2MP Outdoor Bullet AI Camera



Technical Specifications

System Information	
CPU	Multimedia SoC (System-on-Chip)
Flash	8 GB
RAM	1 GB

Camera Specifications

Image Sensor	1/2.8" Progressive CMOS
Max. Resolution	1920x1080 (2MP)
Lens Type	Motorized, Vari-focal, Remote Focus
Focal Length	f = 5 ~ 50 mm
Aperture	F2.0
Iris Type	DC-iris
Field of View	47° ~ 8° (Horizontal) 26° ~ 5° (Vertical) 55° ~ 9° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Day/Night	Yes
Removable IR-cut filter	Yes
Illuminators	Built-in IR illuminators, effective up to 100 meters with Smart IR II, IR LED*4 (30IRE)
Minimum Illumination	0.040 lux @ F2.0 (Color)(30IRE) 0.085 lux @ F2.0 (Color)(50IRE) <0.005 lux @ F2.0 (B/W) 0 lux with IR illumination on
Pan Range	±180°
Tilt Range	90°
Rotation Range	±180°
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built-in)
Storage	Seamless Recording to MicroSD/SDHC/SDKC card (1TB Capacity Supported) and recording to network-attached storage (NAS)
Built-in Installation Aids	Remote focus, remote zoom, Micro USB*, pixel calculator *Requires Wi-Fi dongle and Micro B converter

Video

Compression	H.265, H.264, MJPEG
Maximum Frame Rate	30 fps @ 1920x1080 (WDR Pro on) 60 fps @ 1920x1080 (WDR Pro off)
Maximum Streams	3 video streams (Up to 8 configurable profiles)
S/N Ratio	49 dB
Dynamic Range	120 dB
Video Streaming	Adjustable resolution, quality and constant bit rate control, Smart Stream III
	General settings video title and time stamp overlay, video orientation (flip, mirror, rotation), day/night settings
	Illuminators illuminators, anti-overexposure
	Image settings white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR, EIS (built-in gyro sensor), scene mode (auto, deblur)
Image Settings	Exposure BLC, HLC, exposure control (exposure level, iris adjustment, exposure time, gain control, iris mode), AE speed adjustment, WDR
	Focus zoom, focus
	Privacy mask Pixel calculator Scheduled profile settings

Audio	
Audio Capability	Two-way audio (Full duplex)
Compression	G.711, G.726, MPEG-2 AAC-LC
Interface	External microphone input External line output

Network	
Users	Live viewing for up to 10 clients
Security	Access list, Account block, Audit log, Configurable password strength protection, CSRF protection, Digest authentication, HTTPS, IEEE 802.1x, Secure boot, Session timeout, Signed firmware, Trend Micro IoT Security (Brute force attack event, Cyberattack event, Quarantine event), User access log, User account management
Protocols	802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP/SFTP, HTTP/HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTP, PPPoE, QoS (CoS/DSCP), RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS 1.2, UDP, UPnP
Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Profile G, S, T supported, specification available at www.onvif.org

AI Analytics	
Compute Capability	SoC with built-in hardware deep learning accelerator
Vision Object Analytics	Object Detection people, vehicle (4-wheeled) Path Extraction
Application	Deep Learning VCA (Smart Motion Detection, Smart VCA) Smart Motion Detection (Five-window video motion detection, People detection, Vehicle detection, Time filter), Smart VCA (Intrusion detection, Loitering detection, Line crossing detection, Unattended object detection, Missing object detection, Face detection, Crowd detection)
Application available with license	Running detection, Parking Violation Detection, Restricted Zone Detection Support for more analytic applications and free trial, please visit vivotek.com/video-analytics

Solution Integration	
VADP Package	Stratocast, Trend Micro IoT Security (3-year free trial)
Video motion detection	Motion Detection (Five-window video motion detection)

Alarm and Event	
Event Trigger	Audio detection, camera tampering detection, cybersecurity events (brute force attack event, cyberattack event, quarantine event), digital input, manual trigger, motion detection, periodical trigger, recording notification, SD card life expectancy, shock detection, system boot
Event Action	Event notification via audio clip, camera link, digital output, email, HTTP, FTP/SFTP, NAS server, SD card File upload via email, HTTP, FTP/SFTP, NAS server, SD card

General

	Default I/O RJ-45 cable connector for 10/100 Mbps PoE network connection Audio line input Audio line output DC 12V power input Digital input Digital output DO+ 12V, 50mA
Connectors	DO- 30V, Open Drain, 1A) Micro USB Module I/O* Digital input*2 Digital output*2 (DO+: 12V, 50mA; DO-: 30V, Open Drain, 1A) AC 24V power input *Requires extension I/O module kit
LED Indicator	System power and status indicator
Power Input	AC 24V*, DC 12V, IEEE 802.3af PoE Class 0 (Power Redundancy) *Requires extension I/O module kit
Power Consumption	PoE: Max. 10.77/7.77 W (IR on/off) DC 12V: Max. 9.24/6.24 W (IR on/off) AC 24V*: Max. 10.3/7.3 W (IR on/off) *Requires extension I/O module kit
Dimensions	ø 153 x 288 mm
Weight	2.0 kg
Certifications	EMC CE (EN 55032 Class A, EN 55035, EN 50121-4), FCC (FCC Part 15 Subpart B Class A), RCM (AS/NZS CISPR 32 Class A), VCCI (VCCI-CISPR 32 Class A), ICES-003 Issue 7 Safety UL (UL 62368-1), CB (IEC/EN 62368-1, IEC/EN 60950-22, IEC/EN 62471) Environment IK10 (IEC 62262), IP66/67 (IEC 60529), NEMA (NEMA 250 Type 4X), IEC 60068-2-11 IA BIS (IS 13252), BSMI (EMC: CNS 13438, Safety: CNS 14336-1)
Operating Temperature	Starting Temperature: -30°C ~ 50°C (-22°F ~ 122°F) Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) (IR off) -40°C ~ 50°C (-40°F ~ 122°F) (IR on)
Humidity	98% RH (non-condensing)

System Requirements

Operating System	Microsoft Windows 10/8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above Internet Explorer 11
Other Players	VLC: 1.1.11 or above

Included Accessories

Packing Contents	Quick installation guide, product labels, alignment sticker, L-shaped wrench, screw pack, waterproof accessory pack, sunshield, I/O cable, adapting plate
------------------	---

DORI (EN 62676-4 Standard)

Detection (25PPM/ 8PPF)	Wide: 93.2 m (302.82 ft) Tele: 585.0 m (1,919.29 ft)
Observation (63PPM/ 19PPF)	Wide: 37.0 m (121.39 ft) Tele: 232.1 m (761.48 ft)
Recognition (125PPM/ 38PPF)	Wide: 18.6 m (61.02 ft) Tele: 117.0 m (383.86 ft)
Identification (250PPM/ 76PPF)	Wide: 9.3 m (30.51 ft) Tele: 58.5 m (191.93 ft)

