

# TR-2508

## DirectCX 8channel H.265 Recorder



Supports Multi Standard Analog Camera  
Up to 240ips Full HD recording  
H.265 encoding , Intelligent Codec Support  
Up to 5MP resolution support

UHD Display with HDMI output  
Full HD Display with HDMI and VGA output  
Long transmission distance over coax cable  
Supports OSD control over Coax

Expandable up to 12TB using 2 SATA interfaces  
Supports one click network configuration through FEN service

### SPECIFICATIONS

VIDEO	
Video Inputs	8 BNC (Multistandard Analog)
Supported Camera Types	5MP20, 5MP12, 4MP30, 4MP15, 3MP30, 3MP18, 1080P30, 1080P25, 720P30, 720P25, CVBS(NTSC/PAL)
Video Outputs	1 HDMI, 1 VGA
Display Resolution	HDMI : 3840 x 2160, 1920 x 1080, 1280 x 1024 VGA : 1920 x 1080, 1280 x 1024
Display Speed	Up to 240ips
Digital Zoom	x2 ~ x7
RECORDING	
Recording Resolution	5MP, 4MP, 3MP, 1920x1080, 1280x720, 960x480, 720x480, 640x360, 960x240, 720x240 480x240, 360x240
Frame Rate	240ips@1080P, 144ips@3MP, 120ips@4MP, 80ips@5MP
Compression	H.265, H.264, Intelligent Codec
Recording Mode	Time-Lapse, Event, Pre-Event, Panic
Trigger Events	Alarm in, Motion detection, Video loss, Text-in
PLAYBACK	
Performance	8ch 1080p synchronous playback
Search Mode	Time-lapse, Event log, Text-in
Digital Zoom	x2 ~ x7
STORAGE	
HDD	SATA x2
Total Capacity	The maximum HDD capacity is updated as new HDD models become available.  For the most recent information, please check <a href="#">here</a> .
Data Export Device	USB HDD, USB Stick
NETWORK	
Client Connection	Fast Ethernet x1
Transmission Speed	30ips@Full HD per channel, same as recording stream
Remote Data Export	IDIS Player, AVI, JPG, BMP
Event Notification	Email (attach clip cbf, mp4), Callback to Remote S/W, Push notification (IDIS Mobile)
Two-way Audio	Yes
Client Viewer	IDIS Center, IDIS Mobile, IDIS Web, IDIS Solution Suite
INTERFACE	
Audio In / Out	4 RCA / 1 RCA + 1 HDMI
Alarm In / Out	8 In / 1 Relay Out
Alarm Reset In	-
Serial Interface	RS232 / RS485(Terminal Block), USB 2.0 x 2(Front x 2)
User Interface	Mouse, IR Remote Control, Front Button, Network Remote Keyboard
GENERAL	
Operating System	Embedded Linux
UNIT Dimensions (W x H x D)	300mm x 67mm x 243.6mm (11.8" x 2.6 x 9.6")
Unit Weight	3.0 kg (with 2 4TB HDD)
Working Temperature	0°C to 40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90%
Power Input	Adaptor Input : 100-240V AC, 50/60Hz, 1.5A, Output : 12V DC, 5A
Power Consumption	12V=, 1.84A, 22.1W
Approvals	FCC, CE, KC
Sequence	Yes
Multiscreen on Spot Monitor	No
Color Control	brightness, constrast, saturation, hue
Record	
Scheduling Method	Simple Mode - schedule-list type (add/remove) , schedule a week by hour, holiday setting  Advanced Mode - each event/time shedule-list type (add/remove), schedule a week by hour, holiday setting
Recording Setup Programmable for each Ca	Yes
ARCHIVE & Data Export	
Archiving	No
NETWORK	
Web Browser Access	Internal, External
Remote PTZ Control	Yes
Remote PTZ Setup	Yes
Remote PTZ Advanced Setup	Yes
Remote Data Export	Clip Player, AVI, JPG, BMP, PNG, TIF, PDF



### PRODUCT IMAGE



### DIMENSIONS

