

VA-9600

Max 96 Supporting CH / 192 AI Resources



Intrusion Detection
Anomaly Detection
Crowd
Fall
Loitering

Object Counting & Detection
Object Left Behind/Removed
Perimeter Monitoring
PPE (mask/uniform)
Restricted Areas

Scene Change
Sensor Integration
Smoke, Fire, Weapon Detection

SPECIFICATIONS

SYSTEM	
IDIS Solution Suite	Compatible with IDLA VA Service
Network Connection	2 GbE RJ-45 Ports (1000Base-T)
Channels available for Analytics	Up to 96ch
GPU	2x NVIDIA RTX 4000 Ada,20GB GDDR6
Operating System	Linux Operation System
SSD	1TB(M.2 Type) for OS
Processor	Intel Xeon Silver 4416+ 2.0GHz to 3.9GHz
Memory	4x32GB DDR5, 128GB
Video Outputs	1 HDMI
USB	3 (1 Front USB 2.0 4 Back)
MECHANICAL	
Form Factor	2U RACK Mount Chassis
Unit Dimension (W x H x D)	482.0mm x 86.80mm x 772.13mm (18.98" x 3.42" x 30.40")
Unit Weight	20.98kg (46.25 lbs)
ELECTRICAL	
Power Input	100-240V~, 50/60 Hz, 6.0 - 3.0A
Power Supply	Single Power
Power Consumption	800W
ENVIRONMENTAL	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	0% to 90%
ACCESSORIES SUPPLIED	
Power Cord	125V 15A
General	
Certifications	FCC, CE

PRODUCT IMAGE



DIMENSIONS