

WWT-P-7200MW

Wisenet WAVE Network Video Recorder



The WWT-P-7200MW client workstation is a micro form factor, easy to deploy solution that can be used on-site or remotely to access your Wisenet WAVE video recorder. The workstation has a 256GB solid state drive for the Windows 10 IoT Enterprise LTSC operating system to provide fast boot and load times.

This micro server offers unrivaled deployment flexibility, allowing for its small chassis to be deployed in any small business environment. An optional VESA mount allows the server to be inconspicuously mounted behind a monitor.

Key Features

- Preloaded and configured with Wisenet WAVE video management system client & tools
- Includes USB mouse and keyboard
- 5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty
- Optional VESA mount



WWT-P-7200MW

| SYSTEM | | |
|-----------------------------------------|-------------------------------------------------------------------------|-----------------------------------------------|
| Video Management Software | Wisenet WAVE | |
| OS Drive Bay | 1 x 256GB M.2.5" SSD | |
| Network Interface | 1 x 1GbE RJ45 Ports | |
| Processor | 1 x Intel® Core™ i7-10700T 2.0Ghz to 4.5Ghz (8 Cores, 16 Threads, 16MB) | |
| Memory | 16GB DDR4 | |
| Operating System | Windows 10 IoT Enterprise LTSC. 2019 | |
| Video Outputs | 2x DisplayPort, 2x DisplayPort to HDMI adapters included | |
| USB Ports | Rear: (2) USB 3.1 Gen 1, (2) USB 2.0; Front: (2) USB 3.1 Gen 1 | |
| Other Ports | 2x 3.5mm audio headset output/input | |
| Keyboard & Mouse | Included | |
| MECHANICAL / ELECTRICAL / ENVIRONMENTAL | | |
| Mechanical | Form Factor | Micro form factor client |
| | Color / Material | Black / Metal & Plastic |
| | Dimensions (WxDxH) | 1.4" x 7.0" x 7.2" (36mm x 178mm x 182mm) |
| Electrical | Weight | 3.04 lbs (1.38 kg) |
| | Power Input | 100 ~ 240V AC |
| | Power Consumption | 65W |
| Environmental | Operating Temperature | 41°F ~ 95°F (5°C ~ 35°C) |
| | Storage Temperature | -40°F ~ 149°F (-40°C ~ 65°C) |
| | Operating Humidity | 20% to 80% relative humidity (non-condensing) |
| Certification | UL, cUL, CB, FCC, | |

* The latest product information / specification can be found at www.hanwhasecurity.com

* Bandwidth performance figures based on performance testing by Hanwha Techwin using Wisenet WAVE



Optional VESA mounting